

Weld-on Lifting Eye RUD VLBS without spring



Информация за продукта

- Suspension ring pivots 180°
- Suspension ring & weld-on-block of the VLBS-U are undetachable
- Suspension ring can be angled into position (VLBS-U)

Маркировка: CE - маркировка

Коефициент на безопасност: 4:1.

Продуктов номер	Код	WLL	Eye diam.Ø mm	T mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Тегло	Delivery time
11.427993115	VLBS-U-1,5t without spring	1,5	25	65	33	66	25	38	40	14	33	14	0,35	12
11.427995346	VLBS-U-2,5t without spring	2,5	27	75	38	77	28	45	47	16	40	16	0,5	12
11.427993116	VLBS-U-4t without spring	4	32	83	42	87	31	51	52	18	46	16	0,72	12
11.427993117	VLBS-U-6,7t without spring	6,7	44	117	61	115	44	67	73	24	60	22,5	1,9	12
11.427993118	VLBS-U-10t without spring	10	55	126	75	129	55	67	71	26,5	60	26,5	2,75	12
11.427993120	VLBS-U-16t without spring	16	69	176	96	192	70	100	106	40	90	26	7,1	12

Чертеж

