

High Dynamic Schakle RUD VIP-Mini-Coupling

Produktinformation



High tensile version with an integrated safety thread in the shackle bracket. Smooth bolt support in the shackle on both sides. The bolt is turnable. No bending strength in the thread (only a securing function).

Optimal adaptation - max. mouth width with the smallest shackle bolt. Owing to the turned clevis connection, it is extensively resistant to bending. Long term securing by driving in the pre-assembled tensioning sleeve.


Special thread, thus distinctive in comparison to other shackle bolts. Pre-assembled connecting bolt and tensioning sleeve.

... [Read more](#)

Sicherheitsbeiwert: 4:1

High Dynamic Schakle RUD VIP-Mini-Coupling

Blaupause



Technische Daten

Code	Tragfähigkeit t	Amm mm	Bmm mm	Cmm mm	Dmm mm	Emm mm	Fmm mm	Gmm mm	T mm	Gewicht (kg)
VMKS-4	0,63	14	8	20	10	30	36	21	42	0,11
VVGSC-6	1,5	17	8	22	10	21	40	28	36	0,13
VVGSC-8	2,5	21	10	26	12	32	48	39	48	0,27
VVGSC-10	4	27	13	34	16	35	62	44	60	0,6
VVGSC-13	6,7	33	17	42	20	41	81	59	78	1,3
VVGSC-16	10	38	21	49	24	49	95	69	96	2,25
VVGSC-20	16	47	27	60	30	57	119	88	108	4,26
VVGSC-22	20	53	30	76	36	72	130	95	132	6,43