Lifting Eye Nut RUD RM

Produktinformation



Octagonal lifting eye approved for lifting. Lifting with an angle of inclination is allowed with reduction of WLL (see diagram at blueprint) but we strongly recommend using the RUD RM lifting eye only for straight lifting.

Applied harmonized norms: DIN EN ISO 12100: 2011-03

... *Read more*

Kennzeichnung: nach Norm, CE-Kennzeichnung
Standard: EN 1677-1

Sicherheitsbeiwert: 4:1
Güteklasse: 8


Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Lifting Eye Nut RUD RM

Blaupause



Technische Daten

Artikel-Nr.	Tragfähigkeit	Gewinde mm	A mm	B mm	C mm	D mm	E mm	T mm	Gewicht
11.4055254	0,1	M6	12	11	10	25	25	34	0,1
11.4055255	0,2	M8	12	11	10	25	25	34	0,1
11.4055258	0,25	M10	12	11	10	25	25	34	0,1
11.4055271	0,4	M12	14	13	12	30	30	41	0,2
11.4055281	0,75	M14	16	15	14	35	35	48	0,3
11.4055460	0,8	M16	16	15	14	35	35	48	0,3
11.4055342	1,2	M18	18	17	16	40	40	55	0,4
11.4055343	1,5	M20	18	17	16	40	40	55	0,35
11.4055387	1,5	M22	22	21	20	50	50	70	0,65
11.4055394	2	M24	22	21	20	50	50	70	0,6
11.4055399	2	M27	28	26	24	60	60	85	1,4
11.4055438	3	M30	28	26	24	60	60	85	1,3
11.407994437	3	M33	37	43	38	90	100	130	5,8
11.4053093	4	M36	40	43	38	90	100	130	5,65
11.407904790	5	M39	37	43	38	90	100	130	5,65
11.4053095	6	M42	40	43	38	90	100	130	5,4
11.4053098	8	M48	40	43	38	90	100	130	5,3

Forankra Polska
office@forankra.pl
+48 91 418 25 91
© November 2026 - All Rights Reserved