



## Lifting Eye RUD VLBG-Z, UNC thread

### Produktinformation

- Captive but exchangeable RUD-Bolt
- Bracket adjustable in force direction
- Comprehensive range of threads

**Kennzeichnung:** nach Norm

**Standard:** EN 1677-1

**Sicherheitsbeiwert:** 4:1

| Tragfähigkeit<br>t | Thread<br>Inch | A<br>mm | B<br>mm | C<br>mm | D<br>mm | E<br>mm | F<br>mm | G<br>mm | H<br>mm | I<br>mm | K<br>mm | L<br>mm | N<br>mm | T<br>mm | Gewicht<br>(kg) | Lieferzeit (in Tagen) |
|--------------------|----------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|-----------------|-----------------------|
| 1                  | 1/2 -13        | 32      | 54      | 34      | 26      | 38      | 10      | 29      | 22      | 75      | 45      | 50      | 32      | 75      | 0,36            | 12                    |
| 1,5                | 5/8 -11        | 33      | 56      | 36      | 30      | 39      | 13,5    | 36      | 24      | 86      | 47      | 60      | 38      | 85      | 0,5             | 12                    |
| 2,5                | 3/4 -10        | 50      | 82      | 54      | 45      | 55      | 16,5    | 43      | 28      | 113     | 64      | 71      | 48      | 110     | 1,3             | 12                    |
| 4                  | 1 -8           | 50      | 82      | 54      | 45      | 67      | 18      | 43      | 41      | 130     | 78      | 84      | 48      | 125     | 1,5             | 12                    |
| 8                  | 1 1/2 -6       | 77      | 122     | 82      | 70      | 97      | 26,5    | 77      | 62      | 205     | 110     | 140     | 87      | 197     | 6,14            | 12                    |

# Blaupause

