

Lifting Eye RUD VWBG-V - with variable length

Produktinformation



- Rotating 360°, pivoting 230°
- Optical markings for easy determination for withdraw from service
- Ball bearing


... [Read more](#)

Sicherheitsbeiwert: 4:1

Güteklasse: 10

Lifting Eye RUD VWBG-V - with variable length

Blaupause



Technische Daten

Artikel-Nr.	Tragfähigkeit t	Gewinde mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	M mm	T mm
-	0,45	M10	8	31	29	33,5	30	10-122	38	M10	78
46030008B	0,6	M12	10	49	35	42	36	12-140	47	M12	107
-	1	M14	13	46	38	48	41	14-160	56	M14	114
-	1,3	M16	13	46	38	48	41	16-180	56	M16	114
-	1,8	M18	13	54	35	62	55	18-83	67	M18	137
-	2	M20	13	54	35	62	55	20-223	67	M20	137
-	2	M22	13	54	35	62	55	22-94	67	M22	137
-	3,5	M24	18	66	40	81	70	24-255	88	M24	173
-	3,5	M27	18	66	40	81	70	27-92	88	M27	173
-	5	M30	22	90	50	99	85	30-330	106	M30	221