

Electric E-winch 250-3000kg Lifting

Produktinformation



Electric winch for lifting with a powerful three-phase motor. It's budget-friendly and strong in its work.

- Winch suitable for lifting (with included limit switch)
- Maintenance free bearings
- Protection classification IP54, insulation class F
- Standard overload protection as from 1000 kg
- Powerfull three-phase motor for multirange voltage:
380 – 415V / 50 Hz or 60Hz
- 1 speed pendant control with 1m cable
- Standard 2 meter power cable including 16A CEEplug
- 1 layer of paint

Options:

- For pulling applications (without included limit switch)
- Pressure roller (PR)
- Grooved drum (GD)
- 2 drum compartment (2D) or multiple up to 8 (XD)
- External limit switch (EL)
- Protection classification IP55 (IP55)

Kennzeichnung: nach Norm, CE-Kennzeichnung

Standard: EN 13157, EN 14492

Artikel-Nr.	Code	Tragfähigkeit t	Hubgeschwindigkeit m/min	Seil Ø mm	Motor kW	Seilaufnahme (m)	Tragfähigkeit oberste Lage (kg)	A1 (mm) mm	A2 (mm) mm	A3 mm mm	A4 mm mm	A5 mm mm	A6 mm mm	A7 mm mm	A8 mm mm	Bmm mm	B1mm mm	Cmm mm	C1 (mm) mm	C2 (mm) mm	Dmm mm	D1mm mm	Gewicht (kg)	Versand (in Tagen) innerhalb von:
5406e- W250	e-W250 Lifting	0,25	5,2	4	0,37	122	109	269	151	222	47	59	146	64	17	550	440	355	190	6	55	150	52	12
5406e- W500	e-W500 Lifting	0,5	5,4	6	0,75	45	247	269	189	222	47	59	146	64	17	550	440	355	190	6	55	150	60	12
5406e- W1000	e-W1000 Lifting	1	3,5	8	1,1	100	570	475	172	405	70	130	265	80	27	610	500	455	255	8	102	220	107	12
5406e- W1500	e-W1500 Lifting	1,5	4,4	10	1,8	55	927	475	211	405	70	130	265	80	27	610	500	455	255	8	102	220	122	12
5406e- W2000	e-W2000 Lifting	2	4,7	12	2	94	998	475	220	405	70	149	241	85	27	700	570	515	260	8	168	325	180	12
5406e- W3000	e-W3000 Lifting	3	3,6	14	3	54	1.957	475	240	405	70	149	241	85	27	700	570	515	260	8	168	325	192	12

Blaupause

