Heavy Duty Air Chain Hoists Red Rooster TMH (10.000, 15.000 & 20.000 kg)

Produktinformation



The Red Rooster TMH series air chain hoists have the highest lifting speed with the lowest headroom on the hoist market. With M4 classification of mechanism this hoist is extremely reliable. This hoist will guarantee the continuity of your process. The TMH hoists are designed with a supporting eye for easy installation.

Standard features:

- Precise variable speed control (cord- and pendant control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

ATEX:

- According to EC Directive 94/9/EC (Ex Classification)

Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately)

... Read more

Kennzeichnung: nach Norm, CE-Kennzeichnung
Standard: EN 14492-2


Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Heavy Duty Air Chain Hoists Red Rooster TMH (10.000, 15.000 & 20.000 kg)

Blaupause



Technische Daten

Tragfähigkeit t	Typ	Anzahl der Stränge	Hubgeschwindigkeit ohne Last (m/min)	Luftverbrauch Senken l/sec	Luftverbrauch Heben l/sec	Hubgeschwindigkeit ohne Last (m/min)	Lowering speed with max.load m/min	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	J mm	K mm	L mm	M mm	N mm	Gewicht (kg)
10	Cord control	2	3,3	71,7	58,3	1,6	3,2	860	463	188	275	221	60	214	266	315	65	ø60	45	351	ø61	206
10	Pendant control	2	3,3	71,7	58,3	1,6	3,2	860	463	188	275	221	60	214	266	315	65	ø60	45	351	ø61	206
15	Cord control	3	2,2	71,7	58,3	1,05	2,1	880	695	635	255	270	52	250	266	315	67	ø84	58	436	ø84	316
15	Pendant control	3	2,2	71,7	58,3	1,05	2,1	880	695	635	255	270	52	250	266	315	67	ø84	58	436	ø84	316
20	Cord control	4	1,6	71,7	58,3	0,8	1,6	1.028	500	150	350	-	64	315	326	387	80	ø110	78	475	ø110	466
20	Pendant control	4	1,6	71,7	58,3	0,8	1,6	1.028	500	150	350	-	64	315	326	387	80	ø110	78	475	ø110	466

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved