

Black Belt Sling™ Extreema® with Dyneema® core

Produktinformation



These Extreema® HMPE soft slings have an extensive track record and a solid global footprint in the heavy lift industry. The Black Belt Sling™ has unparalleled load-bearing capacity, ensuring the safe and efficient lifting of even the heaviest loads.

The core is made of Bio Based Dyneema®, which makes it up to 15 times stronger than steel on a weight-to-weight basis.

The sleeve is an orange PES inner sleeve and is covered with a black knitted Cordura® outer sleeve, which is known for its resistance to abrasions, tears, and scuffs. The black sleeve is repairable.

When to choose this product

Best for:

- Heavy lifting with cranes, shackles, and large connection points
- Environments with high abrasion and repeated handling

Features:

- Lightweight and flexible, easy to handle
- Repairable sleeve
- Does not absorb water
- Floats on water
- Abrasion, tearing and scuff resistant
- Sustainable
- High pressure resistant
- EWL: 0,5m – 65m
- Standard with RFID

... [Read more](#)

Kennzeichnung: CE-Kennzeichnung

Sicherheitsbeiwert: 7:1

Black Belt Sling™ Extreema® with Dyneema® core

Technische Daten

Artikel-Nr.	Tragfähigkeit t	Nutzlänge m
-	12	6
12.20EXCO0150XXX	15	-
-	15	13
-	16	1
-	18	7,5
12.20EXCO0200XXX	20	-
-	20	4,8
-	20	5,14
-	20	1,49
-	20	1,75
-	20	1,91
-	20	2,42
-	25	2,23
-	25	4
-	25	4,75
-	25	5
-	25	1
-	25	3
12.20EXCO0300050	30	5
12.20EXCO0300XXX	30	-
-	30	10,53
-	30	2,01
-	30	2,75
-	30	3
-	30	4
-	30	8
-	30	1
-	30	1,5
-	35	1,5
-	35	1,9
-	35	3,47

Black Belt Sling™ Extreema® with Dyneema® core

Technische Daten

Artikel-Nr.	Tragfähigkeit t	Nutzlänge m
-	35	3,6
-	35	4,5
-	35	5,5
12.20EXCO0400050	40	5
12.20EXCO0400XXX	40	-
-	40	1,73
-	40	10,2
-	40	2,68
-	40	3
-	40	3,25
-	40	4,88
-	40	5,18
-	40	7,96
-	40	9,7
-	40	6,5
-	45	1,8
-	45	4,5
-	45	5
-	45	5,75
-	45	7
12.20EXCO0500XXX	50	-
-	50	1
-	50	1,25
-	50	1,5
-	50	2,4
-	50	2,9
-	50	3
-	50	3,1
-	50	3,42
-	50	3,5
-	50	4

Black Belt Sling™ Extreema® with Dyneema® core

Technische Daten

Artikel-Nr.	Tragfähigkeit t	Nutzlänge m
-	50	4,6
-	50	5
-	50	7
-	50	14
-	55	7,7
-	56	10
-	56	16
-	60	1
-	60	2
-	60	2,4
-	60	2,5
-	60	3
-	60	3,2
-	60	3,3
-	60	3,35
-	60	3,55
-	60	5
-	60	5,8
-	60	9
-	65	14
-	65	2,5
-	65	5
-	70	2,5
12.20EXCO0750050	75	5
12.20EXCO0750XXX	75	-
-	75	0,5
-	75	10
-	75	8
-	80	2,07
-	80	5,5
-	80	6,95

Black Belt Sling™ Extreema® with Dyneema® core

Technische Daten

Artikel-Nr.	Tragfähigkeit t	Nutzlänge m
-	80	1,5
-	80	14
-	90	14
-	90	5
-	90	9
12.20EXCO1000050	100	5
12.20EXCO1000XXX	100	-
-	100	10
-	100	12
-	100	3
-	100	7,3
-	120	2
-	120	27
-	120	3
-	120	4,5
-	120	7
12.20EXCO1250500	125	5
12.20EXCO1250XXX	125	-
-	125	12,8
-	125	2
-	125	4
-	125	6,4
-	125	8
12.20EXCO1500500	150	5
12.20EXCO1500XXX	150	-
-	150	2,5
-	150	4,5
-	150	4,73
-	150	6,8
-	160	27
-	160	7

Black Belt Sling™ Extreema® with Dyneema® core

Technische Daten

Artikel-Nr.	Tragfähigkeit t	Nutzlänge m
-	180	14
-	180	5
-	180	6
-	185	12,87
-	195	14,75
-	195	16
12.20EXCO2000500	200	5
12.20EXCO2000XXX	200	-
-	200	1,5
-	200	12,06
-	200	4
-	200	6
-	200	8
-	217,4	3
-	217,4	3,51
-	220	4
-	250	3
-	250	5
-	250	7
-	269,8	11,7
-	269,8	5,85
-	270	4,41
-	290	3,05