

Multi driven hoist

Produktinformation



Small aluminium multi driven chain hoists with a wide range of lifting applications. Can be used with a drill machine. The drill can be connected with 1.5-3 mtr long operating cable in the hoist, so the load can be easily lifted and lowered with the help of the drill machine.

Can also be used directly from the shaft (8 mm hexagonal) coming out of the side of the hoist frame, either with a drill or manually with a comb or 1/2" ratchet handle. The lifting and lowering speed is directly dependent on the rotation speed of the drill, so the speed is always controlled by the drill's own controls.


The standard lifting height is 3 mtr. Other lifting heights can be supplied quickly. The upper and lower hooks are equipped with a swivel.

... [Read more](#)

Kennzeichnung: CE-Kennzeichnung

Multi driven hoist

Blaupause



Technische Daten

Artikel-Nr.	Tragfähigkeit t	Hubhöhe m	Anzahl der Stränge	Hubgeschwindigkeit m/min.	Lastkette mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H min mm	Gewicht (kg)
43050245F	0,25	3	1	2,2	3,2 x 9	109	84	25	1.500	16	30	8	240	3,5
43050246F	0,5	3	1	2,2	4,3 x 12	122	102	30	1.500	16	30	8	270	5,45
43050250F	1	3	2	1,1	4,3 x 12	122	102	32,3	1.500	16	30	8	350	9,15