



Manhole Clamp

Produktinformation

The manhole clamp is used for the transport and laying of manholes. No adjustment of the clamping range is necessary. Accidents caused by incorrect adjustment are excluded. Due to the holdfast application the clamp must not be lifted when applying and disconnecting.

Features:

- Simple applying and disconnecting by means of holdfast application: clamp must not be lifted manually
- No adjustment of the clamping range
- Huge multiplication guarantees optimum safety
- Manhole clamp SZA for manholes and cones according to DIN 4034 Part 1 and 2
- With spring tension
- With web sling or high-strength chains

Sicherheitsbeiwert: 5:1

Artikel-Nr.	Code	Tragfähigkeit t	Maulweite mm	Gewicht (kg)	Versand (in Tagen) innerhalb von:
44000177B	SZM 1	1	40-120	16	12
44000178B	SZM 1.5	1,5	40-120	28	12
44000179B	SZML 1.5	1,5	40-120	29	12
44000184B	SZM 1.5 K	1,5	40-120	32	12
44000180B	SZA 2	2	60-180	28	12
44000185B	SZA 2K	2	60-180	31	12
44000181B	SZA 3	3	60-180	40	12
44000182B	SZAL 3	3	60-180	41	12
44000186B	SZA 3 K	3	60-180	45	12
44000187B	SZAL 3 K	3	60-180	47	12
44000183B	SZA 4	4	60-180	55	12