

## T-Stecker aus Aluminium



### Produktinformation

Konstruktion: Das ursprüngliche Design der Hülse für verzinkte oder nicht verzinkte Stahlseile.

**Material:** Aluminium

**Kennzeichnung:** nach Norm

**Standard:** EN 13411-3

*except size range*

| Artikel-Nr. | Größe der Aderenhülse mm | Länge mm | Lieferzeit (in Tagen) |
|-------------|--------------------------|----------|-----------------------|
| 10.01T025   | 2,5                      | 12       | 12                    |
| 10.01T03    | 3                        | 14       | 12                    |
| 10.01T035   | 3,5                      | 16       | 12                    |
| 10.01T04    | 4                        | 18       | 12                    |
| 10.01T045   | 4,5                      | 20       | 12                    |
| 10.01T05    | 5                        | 23       | 12                    |

|           |     |     |    |
|-----------|-----|-----|----|
| 10.01T06  | 6   | 27  | 12 |
| 10.01T065 | 6,5 | 29  | 12 |
| 10.01T07  | 7   | 32  | 12 |
| 10.01T08  | 8   | 36  | 12 |
| 10.01T09  | 9   | 40  | 12 |
| 10.01T10  | 10  | 45  | 12 |
| 10.01T11  | 11  | 50  | 12 |
| 10.01T12  | 12  | 54  | 12 |
| 10.01T13  | 13  | 59  | 12 |
| 10.01T14  | 14  | 63  | 12 |
| 10.01T16  | 16  | 72  | 12 |
| 10.01T18  | 18  | 81  | 12 |
| 10.01T20  | 20  | 90  | 12 |
| 10.01T22  | 22  | 99  | 12 |
| 10.01T24  | 24  | 108 | 12 |
| 10.01T26  | 26  | 117 | 12 |
| 10.01T28  | 28  | 126 | 12 |
| 10.01T30  | 30  | 135 | 12 |
| 10.01T32  | 32  | 144 | 12 |
| 10.01T34  | 34  | 153 | 12 |
| 10.01T36  | 36  | 162 | 12 |
| 10.01T38  | 38  | 171 | 12 |
| 10.01T40  | 40  | 180 | 12 |

|          |    |     |    |
|----------|----|-----|----|
| 10.01T44 | 44 | 198 | 12 |
| 10.01T48 | 48 | 216 | 12 |
| 10.01T52 | 52 | 234 | 12 |
| 10.01T56 | 56 | 252 | 12 |
| 10.01T60 | 60 | 270 | 12 |
| 10.01T42 | 42 | 189 | 12 |
| 10.01T46 | 46 | 207 | 12 |
| 10.01T50 | 50 | 225 | 12 |
| 10.01T54 | 54 | 243 | 12 |
| 10.01T58 | 58 | 261 | 12 |