

Kausche DIN 6899 B

Produktinformation

Verzinkte Drahtseilkausche zum Schutz von Seilschlaufen.

Ausführung: Gepresst aus Profilstahl

Oberfläche: Verzinkt



Artikel-Nr.	Seildurchmesser mm	a (mm)	b (mm)	c (mm)	d mm	e (mm)	Gewicht kg/100 Stück	Lieferzeit (in Tagen)
10.25B6889903	2,5	3	22	19	12	1,6	0,6	12
10.25B6889904	3,5	4	26	21	13	1,6	0,7	12
10.25B6889905	4	5	32	23	14	1,9	0,9	12
10.25B6889906	5	6	38	25	16	2,4	1,8	12
10.25B6889907	6	7	44	28	18	2,4	1,9	12
10.25B6889908	7	8	51	32	20	2,8	2,7	12
10.25B6889910	9	10	57	38	24	3,1	4,1	12
10.25B6889912	11	12	64	45	28	3,3	6,9	12

10.25B689913	12	13	70	48	30	3,3	7,6	12
10.25B689914	13	14	76	51	32	3,7	9,2	12
10.25B689916	15	16	83	58	36	3,8	16,4	12
10.25B689917	16	17	89	61	38	4,7	19	12
10.25B689918	17	18	95	64	40	4,7	20,3	12
10.25B689920	18	20	102	72	45	5,7	27,3	12
10.25B689922	20	22	114	80	50	5,7	28,6	12
10.25B689924	22	24	127	90	56	6,5	44,8	12
10.25B689926	24	26	140	99	62	6,8	57,7	12
10.25B689928	26	28	152	112	70	8	72	12
10.25B689936	34	36	216	160	100	8,5	176	12
10.25B689938	36	38	229	176	110	8,5	195	12
10.25B689940	38	40	241	184	115	10,5	292	12
10.25B689942	40	42	254	192	120	10,5	320	12
10.25B689945	42	45	305	240	150	10,5	364	12
10.25B689950	47	50	360	265	160	12	535	12
10.25B689960	57	60	380	275	170	12	790	12
10.25B689965	63	65	420	300	180	13	830	12
10.25B689975	72	75	460	350	200	15	1.200	12
10.25B689999	97	100	550	380	220	20	3.050	12

Blaupause

