



Chain Sling G80 4-leg with Foundry Hooks and Grab Hooks

Product information

High quality 4-leg chain sling equipped with foundry hooks with shortening hooks. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Safety factor: 4:1

Grade: 8

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg	Delivery time
42071426W	6	2.36	0.5	14.93	12
42071431W	6	2.36	1	16.53	12
42071429W	6	2.36	1.5	18.13	12
42070362W	6	2.36	2	19.73	12
42070244W	6	2.36	2.5	21.33	12
42070335W	6	2.36	3	22.93	12

42071440W	6	2.36	3.5	24.53	12
42071447W	6	2.36	4	26.13	12
42071451W	6	2.36	5	29.33	12
42071455W	6	2.36	6	32.53	12
42071459W	8	4.25	0.5	21.474	12
42071464W	8	4.25	1	24.174	12
42071463W	8	4.25	1.5	26.874	12
42071467W	8	4.25	2	29.574	12
42070256W	8	4.25	2.5	32.274	12
42071471W	8	4.25	3	34.974	12
42071469W	8	4.25	3.5	37.674	12
42070086W	8	4.25	4	40.374	12
42071476W	8	4.25	5	47.474	12
42071480W	8	4.25	6	52.874	12
42071328W	10	6.7	0.5	27.76	12
42071336W	10	6.7	1	32.06	12
42071332W	10	6.7	1.5	36.36	12
42071339W	10	6.7	2	40.66	12
42070337W	10	6.7	2.5	44.96	12
42070332W	10	6.7	3	49.26	12
42071341W	10	6.7	3.5	53.56	12
42071345W	10	6.7	4	57.86	12
42071348W	10	6.7	5	66.46	12

42071351W	10	6.7	6	75.06	12
42071354W	13	11.2	0.5	44.69	12
42071362W	13	11.2	1	51.69	12
42071358W	13	11.2	1.5	58.69	12
42071369W	13	11.2	2	65.69	12
42071365W	13	11.2	2.5	72.69	12
42070333W	13	11.2	3	82.24	12
42071371W	13	11.2	3.5	89.24	12
42071376W	13	11.2	4	96.24	12
42071379W	13	11.2	5	110.24	12
42071383W	13	11.2	6	124.24	12
42071395W	16	17	1	86.67	12
42071391W	16	17	1.5	97.67	12
42071403W	16	17	2	108.67	12
42071399W	16	17	2.5	119.67	12
42071410W	16	17	3	130.67	12
42071406W	16	17	3.5	141.67	12
42071414W	16	17	4	152.67	12
42071418W	16	17	5	174.67	12
42071422W	16	17	6	196.67	12

Blueprint

