



## Chain Sling G80 3-leg with Safety Hooks and Grab Hooks

### Product information

High quality 3-leg chain sling equipped with self-locking hooks with shortening hooks. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +200°C / 400°C = WLL 75%

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Safety factor:** 4:1

**Grade:** 8

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg	Delivery time
42070691W	6	2.36	0.5	16.91	12
42070699W	6	2.36	2	17.11	12
42070695W	6	2.36	1	18.11	12
42070697W	6	2.36	2.5	18.31	12
42070693W	6	2.36	1.5	19.31	12
42070703W	6	2.36	3	22.91	12

42070701W	6	2.36	3.5	24.11	12
42070707W	6	2.36	5	24.31	12
42070705W	6	2.36	4	25.31	12
42070709W	6	2.36	6	28.41	12
42070711W	8	4.25	0.5	18.448	12
42070715W	8	4.25	1	20.473	12
42070713W	8	4.25	1.5	22.498	12
42070719W	8	4.25	2	24.523	12
42070717W	8	4.25	2.5	26.548	12
42070723W	8	4.25	3	28.573	12
42070721W	8	4.25	3.5	30.598	12
42070725W	8	4.25	4	32.623	12
42070727W	8	4.25	5	36.673	12
42070729W	8	4.25	6	40.723	12
42070631W	10	6.7	0.5	22.075	12
42070635W	10	6.7	1	25.3	12
42070633W	10	6.7	1.5	28.525	12
42070639W	10	6.7	2	31.75	12
42070637W	10	6.7	2.5	34.975	12
42070643W	10	6.7	3	38.2	12
42070641W	10	6.7	3.5	41.425	12
42070645W	10	6.7	4	44.65	12
42070647W	10	6.7	5	51.1	12

42070649W	10	6.7	6	57.55	12
42070651W	13	11.2	0.5	36.42	12
42070655W	13	11.2	1	41.67	12
42070653W	13	11.2	1.5	46.92	12
42070659W	13	11.2	2	52.17	12
42070657W	13	11.2	2.5	57.42	12
42070663W	13	11.2	3	62.67	12
42070661W	13	11.2	3.5	67.92	12
42070665W	13	11.2	4	73.17	12
42070667W	13	11.2	5	83.67	12
42070669W	13	11.2	6	94.17	12
42070675W	16	17	1	69.1	12
42070673W	16	17	1.5	77.35	12
42070679W	16	17	2	85.6	12
42070677W	16	17	2.5	93.85	12
42070683W	16	17	3	102.1	12
42070681W	16	17	3.5	110.35	12
42070685W	16	17	4	118.6	12
42070687W	16	17	5	135.1	12
42070689W	16	17	6	151.6	12

## Blueprint

