

Chain Sling G80 3-leg with Foundry Hooks and Grab Hooks

Product information



High quality 3-leg chain sling equipped with foundry hooks with shortening hooks. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Safety factor: 4:1

Grade: 8

Chain Sling G80 3-leg with Foundry Hooks and Grab Hooks

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42071254W	6	2.36	0.5	13.31
42071261W	6	2.36	1	14.51
42071258W	6	2.36	1.5	15.71
42071268W	6	2.36	2	16.91
42071264W	6	2.36	2.5	18.11
42071276W	6	2.36	3	19.31
42071272W	6	2.36	3.5	20.51
42071279W	6	2.36	4	21.71
42071283W	6	2.36	5	24.11
42071287W	6	2.36	6	26.51
42071291W	8	4.25	0.5	19.318
42071298W	8	4.25	1	21.343
42071295W	8	4.25	1.5	23.368
42071305W	8	4.25	2	25.393
42071302W	8	4.25	2.5	27.418
42071313W	8	4.25	3	29.443
42071309W	8	4.25	3.5	31.468
42071316W	8	4.25	4	33.493
42071320W	8	4.25	5	37.543
42071324W	8	4.25	6	41.593
42071138W	10	6.7	0.5	23.695
42071146W	10	6.7	1	26.92

Chain Sling G80 3-leg with Foundry Hooks and Grab Hooks

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42071142W	10	6.7	1.5	30.145
42071153W	10	6.7	2	33.37
42071150W	10	6.7	2.5	36.595
42071160W	10	6.7	3	39.82
42071156W	10	6.7	3.5	43.045
42071163W	10	6.7	4	46.27
42071167W	10	6.7	5	52.72
42071171W	10	6.7	6	59.17
42071175W	13	11.2	0.5	37.68
42071183W	13	11.2	1	42.93
42071179W	13	11.2	1.5	48.18
42071191W	13	11.2	2	53.43
42071187W	13	11.2	2.5	58.68
42071199W	13	11.2	3	63.93
42071195W	13	11.2	3.5	69.18
42071202W	13	11.2	4	74.43
42071206W	13	11.2	5	84.93
42071210W	13	11.2	6	95.43
42071222W	16	17	1	68.89
42071218W	16	17	1.5	77.14
42071230W	16	17	2	85.39
42071226W	16	17	2.5	93.64
42071238W	16	17	3	105.29
42071234W	16	17	3.5	113.54
42071242W	16	17	4	121.79
42071246W	16	17	5	138.29
42071250W	16	17	6	154.79