

Chain Sling G80 3-leg with Foundry Hooks



Product information

High quality 3-leg chain sling equipped with foundry hooks. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Safety factor: 4:1

Grade: 8

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg	Delivery time
42071253W	6	2.36	0.5	16.29	12
42071260W	6	2.36	1	17.49	12
42071257W	6	2.36	1.5	18.69	12
42071267W	6	2.36	2	19.89	12
42071263W	6	2.36	2.5	21.09	12
42071275W	6	2.36	3	22.29	12
42071271W	6	2.36	3.5	23.49	12

42071278W	6	2.36	4	24.69	12
42071282W	6	2.36	5	27.09	12
42071286W	6	2.36	6	29.49	12
42071290W	8	4.25	0.5	20.283	12
42071297W	8	4.25	1	22.308	12
42071294W	8	4.25	1.5	24.333	12
42071304W	8	4.25	2	26.358	12
42071301W	8	4.25	2.5	28.383	12
42071312W	8	4.25	3	30.408	12
42071308W	8	4.25	3.5	32.433	12
42071315W	8	4.25	4	34.458	12
42071319W	8	4.25	5	38.508	12
42071323W	8	4.25	6	42.558	12
42071145W	10	6.7	1	27.52	12
42071137W	10	6.7	0.5	29.395	12
42071141W	10	6.7	1.5	30.745	12
42071152W	10	6.7	2	31.42	12
42071149W	10	6.7	2.5	37.195	12
42071159W	10	6.7	3	37.87	12
42071155W	10	6.7	3.5	43.645	12
42071162W	10	6.7	4	49.42	12
42071166W	10	6.7	5	50.77	12

42071170W	10	6.7	6	57.22	12
42071174W	13	11.2	0.5	36.06	12
42071182W	13	11.2	1	41.31	12
42071178W	13	11.2	1.5	46.56	12
42071190W	13	11.2	2	51.81	12
42071186W	13	11.2	2.5	57.06	12
42071198W	13	11.2	3	62.31	12
42071194W	13	11.2	3.5	67.56	12
42071201W	13	11.2	4	72.81	12
42071205W	13	11.2	5	83.31	12
42071209W	13	11.2	6	93.81	12
42071221W	16	17	1	55.49	12
42071217W	16	17	1.5	63.74	12
42071229W	16	17	2	71.99	12
42071225W	16	17	2.5	80.24	12
42071237W	16	17	3	88.49	12
42071233W	16	17	3.5	96.74	12
42071241W	16	17	4	104.99	12
42071245W	16	17	5	121.49	12
42071249W	16	17	6	137.99	12

Blueprint

