



Chain Sling G80 1-leg with Safety Hook

Product information

High quality 1-leg chain sling equipped with self-locking hook. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Safety factor: 4:1

Grade: 8

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg	Delivery time
42070515W	6	1.12	0.5	10.27	12
42070197W	6	1.12	1	10.67	12
42070517W	6	1.12	1.5	11.07	12
42070141W	6	1.12	2	11.47	12
42070520W	6	1.12	2.5	11.87	12
42070524W	6	1.12	3	12.27	12
42070522W	6	1.12	3.5	12.67	12

42070526W	6	1.12	4	13.07	12
42070528W	6	1.12	5	13.87	12
42070530W	6	1.12	6	14.67	12
42070532W	8	2	0.5	12.801	12
42070198W	8	2	1	13.476	12
42070534W	8	2	1.5	14.151	12
42070539W	8	2	2	14.826	12
42070537W	8	2	2.5	15.501	12
42070543W	8	2	3	16.176	12
42070541W	8	2	3.5	16.851	12
42070544W	8	2	4	17.526	12
42070546W	8	2	5	18.876	12
42070548W	8	2	6	20.226	12
42070460W	10	3.15	0.5	19.425	12
42070164W	10	3.15	1	20.5	12
42070177W	10	3.15	1.5	21.575	12
42070466W	10	3.15	2	22.65	12
42070464W	10	3.15	2.5	23.725	12
42070470W	10	3.15	3	24.8	12
42070468W	10	3.15	3.5	25.875	12
42070472W	10	3.15	4	26.95	12
42070476W	10	3.15	6	28.7	12

42070474W	10	3.15	5	29.1	12
42070478W	13	5.3	0.5	17.35	12
42070482W	13	5.3	1	19.1	12
42070480W	13	5.3	1.5	20.85	12
42070318W	13	5.3	2	22.6	12
42070484W	13	5.3	2.5	24.35	12
42070489W	13	5.3	3	26.1	12
42070487W	13	5.3	3.5	27.85	12
42070491W	13	5.3	4	29.6	12
42070493W	13	5.3	5	33.1	12
42070495W	13	5.3	6	36.6	12
42070501W	16	8	1	33.7	12
42070499W	16	8	1.5	36.45	12
42070303W	16	8	2	39.2	12
42070503W	16	8	2.5	41.95	12
42070508W	16	8	3	44.7	12
42070511W	16	8	5	45.5	12
42070506W	16	8	3.5	47.45	12
42070510W	16	8	4	50.2	12
42070513W	16	8	6	51	12

Blueprint

