



Chain Sling G80 1-leg with Foundry Hook

Product information

High quality 1-leg chain sling equipped with foundry hook. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Safety factor: 4:1

Grade: 8

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg	Delivery time
42070922W	6	1.12	0.5	10.77	12
42070928W	6	1.12	1	11.17	12
42070925W	6	1.12	1.5	11.57	12
42070006W	6	1.12	2	11.97	12
42070929W	6	1.12	2.5	12.37	12
42070936W	6	1.12	3	12.77	12
42070933W	6	1.12	3.5	13.17	12

42070940W	6	1.12	4	13.57	12
42070944W	6	1.12	5	14.37	12
42070948W	6	1.12	6	15.17	12
42070952W	8	2	0.5	13.091	12
42070959W	8	2	1	13.766	12
42070955W	8	2	1.5	14.441	12
42070965W	8	2	2	15.116	12
42070962W	8	2	2.5	15.791	12
42070971W	8	2	3	16.466	12
42070968W	8	2	3.5	17.141	12
42070973W	8	2	4	17.816	12
42070977W	8	2	5	19.166	12
42070981W	8	2	6	20.516	12
42070810W	10	3.15	0.5	12.315	12
42070823W	10	3.15	2	15.54	12
42070814W	10	3.15	1.5	17.015	12
42070817W	10	3.15	1	21.04	12
42070826W	10	3.15	3.5	21.315	12
42070820W	10	3.15	2.5	24.265	12
42070834W	10	3.15	4	24.94	12
42070830W	10	3.15	3	25.34	12
42070837W	10	3.15	5	29.64	12

42070841W	10	3.15	6	31.79	12
42070845W	13	5.3	0.5	17.77	12
42070852W	13	5.3	1	19.52	12
42070849W	13	5.3	1.5	21.27	12
42070859W	13	5.3	2	23.02	12
42070856W	13	5.3	2.5	24.77	12
42070867W	13	5.3	3	26.52	12
42070863W	13	5.3	3.5	28.27	12
42070870W	13	5.3	4	30.02	12
42070874W	13	5.3	5	33.52	12
42070878W	13	5.3	6	37.02	12
42070890W	16	8	1	23.43	12
42070886W	16	8	1.5	26.18	12
42070898W	16	8	2	28.93	12
42070894W	16	8	2.5	31.68	12
42070906W	16	8	3	34.43	12
42070902W	16	8	3.5	37.18	12
42070910W	16	8	4	39.93	12
42070914W	16	8	5	45.43	12
42070918W	16	8	6	50.93	12

Blueprint

