Lifting Eye Nut RUD RM, UNC thread

Product information



- considerably higher WLL in comparison to DIN 582
- clear marking of the minimum WLL
- comprehensive range of threads

... *Read more*

Marking: According to standard
Temperature range: -40°C up to +200°C
Standard: EN 1677-1

Safety factor: 4:1

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Lifting Eye Nut RUD RM, UNC thread

Blueprint



Technical data

WLL ton	Thread Inch	A mm	B mm	C mm	D mm	E mm	T mm	Weight kg
0.2	3/8 -16	12	11	10	25	25	34	0.1
0.35	1/2 -13	14	13	12	30	30	41	0.17
0.75	5/8 -11	16	15	14	35	35	48	0.26
1.2	3/4 -10	18	17	16	40	40	55	0.39
1.5	7/8 -9	22	21	20	50	50	70	0.7
2	1 -8	28	26	24	60	60	85	1.4
3	1 1/4 -7	28	26	24	60	60	85	1.35

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved