# Lifting Eye RUD VWBG

**Product information**



- Rotates 360°, pivots 230°
- Indicator markings to highlight wear and damage to load ring
- Oversized load rings
- Ball bearing

... *Read more*

**Marking:** According to standard, CE-mark
**Temperature range:** -40°C up to +100°C
**Standard:** EN 1677-1, EN 1677-4

**Safety factor:** 4:1

**Forankra Polska**
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

# Lifting Eye RUD VWBG

## Blueprint




## Technical data

| Part code | WLL | Thread mm | A mm | B mm | C mm | D mm | E mm | F mm | G mm | M mm | T mm | Weight |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| - | 8 | M36 | 22 | 86 | 50 | 90 | 80 | 54 | 94 | M36 | 208 | 4.72 |
| - | 12 | M42 | 26 | 111 | 65 | 98 | 85 | 63 | 95 | M42 | 234 | 6.1 |
| - | 12 | M45 | 26 | 11 | 65 | 98 | 85 | 67 | 95 | M45 | 234 | 6.24 |
| - | 13 | M48 | 26 | 111 | 65 | 98 | 85 | 68 | 95 | M48 | 234 | 6.37 |
| - | 14 | M52 | 32 | 119 | 70 | 120 | 95 | 78 | 120 | M52 | 271 | 10.55 |
| 11.427999004 | 16 | M56 | 32 | 119 | 70 | 120 | 95 | 84 | 120 | M56 | 271 | 10.68 |
| - | 16 | M64 | 32 | 119 | 70 | 120 | 95 | 94 | 120 | M64 | 271 | 11.4 |
| - | 31.5 | M72 | 46 | 130 | 90 | 170 | 145 | 108 | 159 | M72 | 338 | 29.96 |

**Forankra Polska**
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved