

Weld-on Lifting Ring RUD VRBS-FIX

Product information

Load ring for plane surfaces. 180° pivoting.

Marking: According to standard, CE-marked

Temperature range: -20°C to +200°C.

Finish: Pink powder coated.






Standard: EN 1677-1

Safety factor: 4:1



Part code	WLL ton	A,	B,	C,	D,	E,	F,	T mm	Weight kg	Delivery time
11.427999019	4	62	14	28	48	135	71	65	0.77	12
11.427999020	6.7	88	20	39	60	170	92	84	1.64	12
11.427999021	10	100	22	46	65	195	100	95	2.62	12
11.427999301	16	130	30	57	90	263	134	127	5.53	12
11.427999302	31.5	160	42	78	130	373	195	178	15.6	12

Technical data

Method of lift										
Number of legs	1	1	2	2	2	2	2	3 / 4	3 / 4	3 / 4
Angle of inclination β	0°	90°	0°	90°	0-45°	>45-60°	Un-symm.	0-45°	>45-60°	Un-symm.
Factor	1	1	2	2	1.4	1	1	2.1	1.5	1
Type	For the max. total load weight >G< in metric tons									
VRBS 4 t	4 t	4 t	8 t	8 t	5.6 t	4 t	4 t	8.4 t	6 t	4 t
VRBS 6.7 t	6.7 t	6.7 t	13.4 t	13.4 t	9.4 t	6.7 t	6.7 t	14.1 t	10 t	6.7 t
VRBS 10 t	10 t	10 t	20 t	20 t	14 t	10 t	10 t	21.2 t	15 t	10 t
VRBS 16 t	16 t	16 t	32 t	32 t	22.4 t	16 t	16 t	33.6 t	24 t	16 t
VRBS 31.5 t	31.5 t	31.5 t	63 t	63 t	45 t	31.5 t	31.5 t	67 t	47.5 t	31.5 t
VRBS 50 t	50 t	50 t	100 t	100 t	70 t	50 t	50 t	105 t	75 t	50 t

Blueprint

