

Goliath Lifting Loop 40.8

Product information



Goliath lifting loop with forged head for lifting and transporting.

The head must be screwed on tightly.

Every loop within the Schroeder lifting socket system carries a tag showing the manufacturer, thread and load group, ensuring correct identification.

The tags for identifying

- means of lifting (lifting loops) and

- lifting sockets

as well as the nailing plates have the same colour for each thread size.

The requirements of the "Safety rules for lifting sockets and systems for precast concrete elements" plus the instructions for installation and use must be complied with.

This product complies with the requirements of the European Machinery Directive 2006/42/EC.

Marking: According to standard, Manufacturer ID, thread and load group

Standard: CEN/TR 15728 - VDI/BV-BS 6205

Safety factor: 4:1

Thread mm	Load grp. t	Length mm	d mm	L mm	D mm	g mm	k mm	s mm	Weight kg	Delivery time
M10	0.4	335	M10	335	24	15	60	8	0.4	12
M12	0.5	335	M12	335	24	15	60	8	0.4	12
M16	1.2	365	M16	365	24	20	60	9	0.5	12
M20	2	470	M20	470	24	25	102	12	1.57	12
M24	2.5	550	M24	550	44	30	102	14	2.1	12
M30	4	590	M30	590	44	35	102	16	2.6	12
M36	6.3	780	M36	780	75	50	170	20	7.68	12

Blueprint

