



Heavy Duty Air Chain Hoists Red Rooster TMH (25.000 & 30.000 kg)

Product information

The Red Rooster TMH series air chain hoists have the highest lifting speed with the lowest headroom on the hoist market. With classification of mechanism, M3 for the TMH-25 and M2 for the TMH-30, these hoists are extremely reliable. This hoist will guarantee the continuity of your process.

Standard features:

- Precise variable speed control (cord control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Low noise level (84 dBA)
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

ATEX:

- According to EC Directive 94/9/EC (Ex Classification)

Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

Marking: According to standard, CE-marked

Standard: EN 14492-2

Part code	WLL ton	Type	Chain falls	Lifting speed without load m/min	Air consumption lowering (l/sec)	Air consumption lifting l/sec	Lifting speed with max.load m/min	Lowering speed with max.load m/min	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	J mm	K mm	L mm	M mm	N mm	O mm	P mm	Q mm	R mm	Weight kg	Delivery time
5601TMH25TC2	25	Cord control	2	2.7	180	108	1.4	3	1,290	566	223	343	330	82	285	708	352	356	90	∅100	71	732	558	71	100	90	581	12
5601TMH25TP2E	25	Pendant control	2	2.7	180	108	1.4	3	1,290	566	223	343	330	82	285	708	352	356	90	∅100	71	732	558	71	100	90	581	12
5601TMH30TC2	30	Cord control	2	2.7	167	108	1	2.7	1,290	566	223	343	330	82	285	708	352	356	90	∅100	71	732	558	71	100	90	581	12
5601TMH30TP2E	30	Pendant control	2	2.7	167	108	1	2.7	1,290	566	223	343	330	82	285	708	352	356	90	∅100	71	732	558	71	100	90	581	12

Blueprint

