

Triangle link for webbing DB type 2

Product information



The Triangle Link for Webbing DB Type 2 is a robust female component designed for use in textile slings. It is intended for sling terminations, providing a stable and secure termination. Made from durable materials, the D-ring is load-resistant and offers reliability in demanding work conditions. This product is ideal for industrial and construction lifting applications, meeting high standards of quality and safety.

Marking: According to standard

Finish: Galvanized

Standard: EN 1677

Safety factor: 6:1

Part code	Code	WLL ton	Dimensions mm	D1 mm	D2 mm	B mm	H1 mm	H2 mm	Weight kg	Delivery time
42040451B	DB01	1	80x100 (BxH1)	12	30	80	100	25	0.4	2
42040452B	DB02	2	115x146 (BxH1)	16	60	115	146	40	1	2
42040453B	DB03	3	160x205 (BxH1)	20	90/100	160	205	55	2	2
42040454B	DB04	4	200x218 (BxH1)	23	120	200	218	55	3.1	2
42040455B	DB05	5	240x300 (BxH1)	26	150	240	300	80	5	2
42040456B	DB06	6	284x284 (BxH1)	28	180	284	284	80	5.4	2
42040457B	DB08	8	370x332 (BxH1)	32	240	370	332	90	10.2	2
42040458B	DB10	10	424x385 (BxH1)	35	300	424	385	100	13.8	2

Blueprint

