Car Lashing VDI 2700 50mm LC 2500daN Standard handle

Product information



An auto transporter belt with a 3-point attachment system that meets VDI 2700 8.1 standards, guaranteeing the safe transport of vehicles. The product provides excellent transmission and uniform distribution of standard tension force (STF). The belt achieves the required performance level of ETA ≥ 0.5. Minimized belt stretch of 4% ensures reliable load stability, reducing the need for re-tensioning during transport.

The 50mm belt kit includes:

- 50mm polyester belt 2,8m
- Tensioner 50mm, LC 2500daN, STF 350daN, dimensions 232x98mm
- 3 swivel hooks
- Grass type cover 1,3m

Features:

- Performance ETA coefficient ≥ 0.5
- Label with certificate number and inspector's label on the so-called grass cover
- Meets the requirements of EN 12195-2
- According to VDI 2700 8.1, the belt strap must not come into contact with the tire when securing the vehicle. Therefore, rubber or rubber-material protection must be used!

... *Read more*

Material: poliester
Note: Stretchability ≤4%
Warning: Not for Lifting!

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Car Lashing VDI 2700 50mm LC 2500daN Standard handle

Technical data

Part code	LC daN	Length m	Band width mm	Fitting	STF daN
25040127F	2,500	2.8	50	Swivel hook	350

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved