

The Original Roundsling Extreema® with Dyneema® core



Product information

The Original EXTREEMA® round sling was the first product created under the EXTREEMA® brand. With its innovative design and unparalleled performance, the Original quickly gained a reputation as a top-of-the-line product in the market, paving the way for the brand's continued success and growth.

Its core is made of Bio-Based Dyneema®, which makes it up to 15 times stronger than steel on a weight-to-weight basis.

The sleeve is white HMPE Extreema® L-series sleeve. With exceptional performance against cuts, abrasions, and punctures. The white sleeve is repairable.

Features:

- Lightweight and flexible, easy to handle
- Repairable sleeve
- Resistant against chemicals
- Does not absorb water
- Floats on water
- Long life cycle
- Sustainable
- WLL: 3t - 600t
- EWL: 0,5m – 65m

Material: Dyneema, HMPE

Marking: CE-marked

Temperature range: -50°C up to +70°C

Safety factor: 7:1

Part code	Code	WLL ton	EWL m	Delivery time

-	-	-	3	4	12
-	-	-	4	3	12
-	-	-	5	1	12
-	-	-	5	4	12
12.20EXL0100XXX	EXL/10/XXX	10	-	-	12
-	-	10	1	-	12
-	-	10	2	-	12
-	-	10	3	-	12
-	-	10	6	-	12
12.20EXL0120XXX	EXL/12/XXX	12	-	-	12
-	-	12	4	-	12
-	-	12	5	-	12
-	-	12	8	-	12
-	-	12	10	-	12
-	-	12	12	-	12
-	-	12	15	-	12
-	-	12	20	-	12
12.20EXL0150XXX	EXL/15/XXX	15	-	-	12
-	-	15	4	-	12
-	-	15	12	-	12
-	-	15	15	-	12
-	-	15	1.5	-	12
-	-	15	2.5	-	12

12.20EXL0200XXX	EXL/20/XXX	20	-	12
-	-	20	1	12
-	-	20	7	12
-	-	20	9	12
-	-	20	10	12
12.20EXL0250XXX	EXL/25/XXX	25	-	12
-	-	25	10	12
-	-	25	6	12
-	-	25	7	12
-	-	25	9	12
-	-	25	12	12
-	-	25	20	12
12.20EXL0300XXX	EXL/30/XXX	30	-	12
-	-	30	3	12
-	-	30	4	12
-	-	30	5	12
-	-	30	6	12
-	-	30	7	12
-	-	30	15	12
-	-	30	18	12
-	-	30	20	12
-	-	30	25	12
12.20EXL0400XXX	EXL/40/XXX	40	-	12

-	-	-	40	15	12
-	-	-	40	8	12
-	-	-	40	10	12
-	-	-	40	12	12
-	-	-	40	15	12
12.20EXL0500XXX	EXL/50/XXX	50	-	-	12
-	-	50	10	-	12
-	-	50	5	-	12
-	-	50	9	-	12
-	-	50	12	-	12
-	-	60	8	-	12
-	-	65	5	-	12
-	-	70	4	-	12
-	-	70	5	-	12
12.20EXL0750XXX	EXL/75/XXX	75	-	-	12
-	-	80	5	-	12
-	-	80	6	-	12
-	-	80	7	-	12
-	-	80	8	-	12
-	-	80	10	-	12
12.20EXL1000XXX	EXL/100/XXX	100	-	-	12
-	-	100	8	-	12
-	-	100	15	-	12

-	-	-	100	20	12
-	-	-	100	3	12
-	-	-	100	4	12
-	-	-	120	5	12
-	-	-	120	7	12
12.20EXL1250XXX	EXL/125/XXX	125	-	-	12
-	-	125	3	-	12
-	-	125	5	-	12
12.20EXL1500XXX	EXL/150/XXX	150	-	-	12
12.20EXL2000XXX	EXL/200/XXX	200	-	-	12

Technical data