

Black Belt Sling™ Extreema® with Dyneema® core

Product information



These Extreema® HMPE soft slings have an extensive track record and a solid global footprint in the heavy lift industry. The Black Belt Sling™ has unparalleled load-bearing capacity, ensuring the safe and efficient lifting of even the heaviest loads.

The core is made of Bio Based Dyneema®, which makes it up to 15 times stronger than steel on a weight-to-weight basis.

The sleeve is an orange PES inner sleeve and is covered with a black knitted Cordura® outer sleeve, which is known for its resistance to abrasions, tears, and scuffs. The black sleeve is repairable.

When to choose this product

Best for:

- Heavy lifting with cranes, shackles, and large connection points
- Environments with high abrasion and repeated handling

Features:

- Lightweight and flexible, easy to handle
- Repairable sleeve
- Does not absorb water
- Floats on water
- Abrasion, tearing and scuff resistant
- Sustainable
- High pressure resistant
- EWL: 0,5m – 65m
- Standard with RFID

Material: PES, Dyneema®

Marking: CE-marked

Temperature range: -40°C up to +70°C

Safety factor: 7:1

Part code	WLL ton	EWL m	Delivery time
-	12	6	12
12.20EXCO0150XXX	15	-	12
-	15	13	12
-	16	1	12
-	18	7.5	12
12.20EXCO0200XXX	20	-	12
-	20	4.8	12
-	20	5.14	12
-	20	1.49	12
-	20	1.75	12
-	20	1.91	12
-	20	2.42	12
-	25	2.23	12
-	25	4	12
-	25	4.75	12
-	25	5	12
-	25	1	12
-	25	3	12
12.20EXCO0300050	30	5	12
12.20EXCO0300XXX	30	-	12
-	30	10.53	12

-	30	2.01	12
-	30	2.75	12
-	30	3	12
-	30	4	12
-	30	8	12
-	30	1	12
-	30	1.5	12
-	35	1.5	12
-	35	1.9	12
-	35	3.47	12
-	35	3.6	12
-	35	4.5	12
-	35	5.5	12
12.20EXCO0400050	40	5	12
12.20EXCO0400XXX	40	-	12
-	40	1.73	12
-	40	10.2	12
-	40	2.68	12
-	40	3	12
-	40	3.25	12
-	40	4.88	12
-	40	5.18	12
-	40	7.96	12

-	40	9.7	12
-	40	6.5	12
-	45	1.8	12
-	45	4.5	12
-	45	5	12
-	45	5.75	12
-	45	7	12
12.20EXCO0500XXX	50	-	12
-	50	1	12
-	50	1.25	12
-	50	1.5	12
-	50	2.4	12
-	50	2.9	12
-	50	3	12
-	50	3.1	12
-	50	3.42	12
-	50	3.5	12
-	50	4	12
-	50	4.6	12
-	50	5	12
-	50	7	12
-	50	14	12
-	55	7.7	12

-	56	10	12
-	56	16	12
-	60	1	12
-	60	2	12
-	60	2.4	12
-	60	2.5	12
-	60	3	12
-	60	3.2	12
-	60	3.3	12
-	60	3.35	12
-	60	3.55	12
-	60	5	12
-	60	5.8	12
-	60	9	12
-	65	14	12
-	65	2.5	12
-	65	5	12
-	70	2.5	12
12.20EXCO0750050	75	5	12
12.20EXCO0750XXX	75	-	12
-	75	0.5	12
-	75	10	12
-	75	8	12

-	80	2.07	12
-	80	5.5	12
-	80	6.95	12
-	80	1.5	12
-	80	14	12
-	90	14	12
-	90	5	12
-	90	9	12
12.20EXCO1000050	100	5	12
12.20EXCO1000XXX	100	-	12
-	100	10	12
-	100	12	12
-	100	3	12
-	100	7.3	12
-	120	2	12
-	120	27	12
-	120	3	12
-	120	4.5	12
-	120	7	12
12.20EXCO1250500	125	5	12
12.20EXCO1250XXX	125	-	12
-	125	12.8	12
-	125	2	12

-	125	4	12
-	125	6.4	12
-	125	8	12
12.20EXCO1500500	150	5	12
12.20EXCO1500XXX	150	-	12
-	150	2.5	12
-	150	4.5	12
-	150	4.73	12
-	150	6.8	12
-	160	27	12
-	160	7	12
-	180	14	12
-	180	5	12
-	180	6	12
-	185	12.87	12
-	195	14.75	12
-	195	16	12
12.20EXCO2000500	200	5	12
12.20EXCO2000XXX	200	-	12
-	200	1.5	12
-	200	12.06	12
-	200	4	12
-	200	6	12

-	200	8	12
-	217.4	3	12
-	217.4	3.51	12
-	220	4	12
-	250	3	12
-	250	5	12
-	250	7	12
-	269.8	11.7	12
-	269.8	5.85	12
-	270	4.41	12
-	290	3.05	12