

Black Belt Sling Extreema® with Dyneema® core

Product information



These EXTREEMA® HMPE soft slings have an extensive track record and a solid global footprint in the heavy lift industry. The Black Belt Sling™ has unparalleled load-bearing capacity, ensuring the safe and efficient lifting of even the heaviest loads.

The core is made of Bio Based Dyneema®, which makes it up to 15 times stronger than steel on a weight-to-weight basis.

The sleeve is an orange PES inner sleeve and is covered with a black knitted Cordura® outer sleeve, which is known for its resistance to abrasions, tears, and scuffs. The black sleeve is repairable.

Features:

- Lightweight and flexible, easy to handle
- Repairable sleeve
- Does not absorb water
- Floats on water
- Abrasion, tearing and scuff resistant
- Sustainable
- High pressure resistant
- EWL: 0,5m – 65m

Material: PES, Dyneema®

Marking: CE-marked

Temperature range: -50°C up to +70°C

Safety factor: 7:1

Part code	WLL ton	EWL m	Delivery time
-	12	6	12
12.20EXCO0150XXX	15	-	12

-		15	13	12
-		16	1	12
-		18	7.5	12
12.20EXCO0200XXX		20	-	12
-		20	4.8	12
-		20	5.14	12
-		20	1.49	12
-		20	1.75	12
-		20	1.91	12
-		20	2.42	12
-		25	2.23	12
-		25	4	12
-		25	4.75	12
-		25	5	12
-		25	1	12
-		25	3	12
12.20EXCO0300050		30	5	12
12.20EXCO0300XXX		30	-	12
-		30	10.53	12
-		30	2.01	12
-		30	2.75	12
-		30	3	12
-		30	4	12

-		30	8	12
-		30	1	12
-		30	1.5	12
-		35	1.5	12
-		35	1.9	12
-		35	3.47	12
-		35	3.6	12
-		35	4.5	12
-		35	5.5	12
12.20EXCO0400050		40	5	12
12.20EXCO0400XXX		40	-	12
-		40	1.73	12
-		40	10.2	12
-		40	2.68	12
-		40	3	12
-		40	3.25	12
-		40	4.88	12
-		40	5.18	12
-		40	7.96	12
-		40	9.7	12
-		40	6.5	12
-		45	1.8	12
-		45	4.5	12

-		45	5	12
-		45	5.75	12
-		45	7	12
12.20EXCO0500XXX		50	-	12
-		50	1	12
-		50	1.25	12
-		50	1.5	12
-		50	2.4	12
-		50	2.9	12
-		50	3	12
-		50	3.1	12
-		50	3.42	12
-		50	3.5	12
-		50	4	12
-		50	4.6	12
-		50	5	12
-		50	7	12
-		50	14	12
-		55	7.7	12
-		56	10	12
-		56	16	12
-		60	1	12
-		60	2	12

-		60	2.4	12
-		60	2.5	12
-		60	3	12
-		60	3.2	12
-		60	3.3	12
-		60	3.35	12
-		60	3.55	12
-		60	5	12
-		60	5.8	12
-		60	9	12
-		65	14	12
-		65	2.5	12
-		65	5	12
-		70	2.5	12
12.20EXCO0750050		75	5	12
12.20EXCO0750XXX		75	-	12
-		75	0.5	12
-		75	10	12
-		75	8	12
-		80	2.07	12
-		80	5.5	12
-		80	6.95	12
-		80	1.5	12

-		80	14	12
-		90	14	12
-		90	5	12
-		90	9	12
12.20EXCO1000050		100	5	12
12.20EXCO1000XXX		100	-	12
-		100	10	12
-		100	12	12
-		100	3	12
-		100	7.3	12
-		120	2	12
-		120	27	12
-		120	3	12
-		120	4.5	12
-		120	7	12
12.20EXCO1250500		125	5	12
12.20EXCO1250XXX		125	-	12
-		125	12.8	12
-		125	2	12
-		125	4	12
-		125	6.4	12
-		125	8	12
12.20EXCO1500500		150	5	12

12.20EXCO1500XXX	150	-	12
-	150	2.5	12
-	150	4.5	12
-	150	4.73	12
-	150	6.8	12
-	160	27	12
-	160	7	12
-	180	14	12
-	180	5	12
-	180	6	12
-	185	12.87	12
-	195	14.75	12
-	195	16	12
12.20EXCO2000500	200	5	12
12.20EXCO2000XXX	200	-	12
-	200	1.5	12
-	200	12.06	12
-	200	4	12
-	200	6	12
-	200	8	12
-	217.4	3	12
-	217.4	3.51	12
-	220	4	12

-		250	3	12
-		250	5	12
-		250	7	12
-		269.8	11.7	12
-		269.8	5.85	12
-		270	4.41	12
-		290	3.05	12