



## Round Sling Extreema® XS

### Product information

The Extreema® XS sling is a compact high-strength round sling designed for lifting operations in confined or restricted spaces. It is used where traditional slings are too bulky or require larger hardware. Manufactured from HMPE, it combines high load capacity with a small diameter, enabling efficient and controlled lifting in tight environments.

WLL range: 3 – 20t

EWL range: 0,5m – 16m, (15t/20t can be made up to 65m)

#### When to choose this product

##### Best for:

- Lifting in confined spaces with limited clearance
- Applications requiring compatibility with standard shackles

##### Product benefits

- Compact diameter enables lifting in restricted or hard-to-reach areas
- D:d ratio 1:1 allows use with standard bow shackles
- HMPE construction provides high strength with low weight
- Lightweight design simplifies transport, handling, and storage
- Seamless sleeve supports durability and extended service life

**Material:** HMPE

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +70°C

**Standard:** EN 1492-2

*except material*

**Safety factor:** 7:1

Part code

WLL  
ton

EWL  
m

Colour

Delivery time

12.20EXHL030005	3	0.5	Yellow	12
12.20EXHL0300075	3	0.75	Yellow	12
12.20EXHL030010	3	1	Yellow	12
12.20EXHL030015	3	1.5	Yellow	12
12.20EXHL030020	3	2	Yellow	12
12.20EXHL030025	3	2.5	Yellow	12
12.20EXHL030030	3	3	Yellow	12
12.20EXHL030040	3	4	Yellow	12
12.20EXHL030050	3	5	Yellow	12
-	3	6	Yellow	12
-	3	7	Yellow	12
-	3	8	Yellow	12
12.20EXHL050005	5	0.5	Red	12
12.20EXHL050010	5	1	Red	12
12.20EXHL050015	5	1.5	Red	12
12.20EXHL050020	5	2	Red	12
12.20EXHL050025	5	2.5	Red	12
12.20EXHL050030	5	3	Red	12
12.20EXHL050040	5	4	Red	12
12.20EXHL050050	5	5	Red	12
-	5	6	Red	12
-	5	7	Red	12
-	5	8	Red	12

12.20EXHL100015	10	1.5	Orange	12
12.20EXHL100020	10	2	Orange	12
12.20EXHL100030	10	3	Orange	12
12.20EXHL100040	10	4	Orange	12
12.20EXHL100050	10	5	Orange	12
-	10	6	Orange	12
-	10	0.5	Orange	12
-	10	7	Orange	12

## Technical data

**Extreema® XS roundsling****HMPE EXS**

<b>WLL</b>	<b>SF</b>	<b>Core ø mm</b>	<b>Weight kg 3m EWL</b>	<b>p/m extra kg</b>
3t	7	9	0,8	0,25
5t	7	14	1,35	0,43
10t	7	23	2	0,65
15t	7	31	3,5	1,15
20t	7	37	4,6	1,50