

Round Sling EXTREEMA® XS



Product information

The XS round slings are the ultimate solution for lifting loads ranging from 1T to 20T. They offer a cost-effective and reliable alternative to traditional polyester slings. Say goodbye to the hassle of disposal, storage, and transportation costs, and welcome a practical and efficient choice that never compromises safety and quality.

Their lightweight design ensures easy handling and transport, making them a practical choice across various lifting applications. By embracing the XS round slings, industries secure a dependable lifting solution and embark on a sustainable journey, reducing industrial waste and minimizing their environmental footprint.

Extreema XS Slings have massive lifting power in a much smaller size with 78% less weight than polyester round slings and 55% smaller diameter, you can lift on the shackle pin. Slings are 8-10 times lighter than steel wire ropes.

Features and benefits:

- Saving costs
- D:d ratio of 1:1
- Environmentally friendly
- Light in weight
- Flexible
- Less storage
- Long life cycle
- Access to limited lifting space
- Safer lifting operations
- Improving workflow
- Available in 3t yellow, 5t red, 10t orange, 15t orange and 20t orange
- Available in effective working lengths in the range of 0.5 m up to 16 m
- Standard with RFID

Material: HMPE -Dyneema®

Marking: According to standard, CE-marked

Temperature range: -50°C up to +70°C

Standard: EN 1492-2

except material

Safety factor: 7:1

Part code	WLL ton	EWL m	Colour	Delivery time
12.20EXHL030005	3	0.5	Yellow	12
12.20EXHL0300075	3	0.75	Yellow	12
12.20EXHL030010	3	1	Yellow	12
12.20EXHL030015	3	1.5	Yellow	12
12.20EXHL030020	3	2	Yellow	12
12.20EXHL030025	3	2.5	Yellow	12
12.20EXHL030030	3	3	Yellow	12
12.20EXHL030040	3	4	Yellow	12
12.20EXHL030050	3	5	Yellow	12
-	3	6	Yellow	12
-	3	7	Yellow	12
-	3	8	Yellow	12
12.20EXHL050005	5	0.5	Red	12
12.20EXHL050010	5	1	Red	12
12.20EXHL050015	5	1.5	Red	12
12.20EXHL050020	5	2	Red	12
12.20EXHL050025	5	2.5	Red	12
12.20EXHL050030	5	3	Red	12
12.20EXHL050040	5	4	Red	12
12.20EXHL050050	5	5	Red	12
-	5	6	Red	12

-	5	7	Red	12
-	5	8	Red	12
12.20EXHL100015	10	1.5	Orange	12
12.20EXHL100020	10	2	Orange	12
12.20EXHL100030	10	3	Orange	12
12.20EXHL100040	10	4	Orange	12
12.20EXHL100050	10	5	Orange	12
-	10	6	Orange	12
-	10	0.5	Orange	12
-	10	7	Orange	12

Technical data

Extreema® XS roundsling**HMPE EXS**

WLL	SF	Core ø mm	Weight kg 3m EWL	p/m extra kg
3t	7	9	0,8	0,25
5t	7	14	1,35	0,43
10t	7	23	2	0,65
15t	7	31	3,5	1,15
20t	7	37	4,6	1,50