



Round Sling EXTREEMA® XS

Product information

The XS round slings are the ultimate solution for lifting loads ranging from 1T to 20T. They offer a cost-effective and reliable alternative to traditional polyester slings. Say goodbye to the hassle of disposal, storage, and transportation costs, and welcome a practical and efficient choice that never compromises safety and quality.

Their lightweight design ensures easy handling and transport, making them a practical choice across various lifting applications. By embracing the XS round slings, industries secure a dependable lifting solution and embark on a sustainable journey, reducing industrial waste and minimizing their environmental footprint.

Extreema XS Slings have massive lifting power in a much smaller size with 78% less weight than polyester round slings and 55% smaller diameter, you can lift on the shackle pin. Slings are 8-10 times lighter than steel wire ropes.

Features and benefits:

- Saving costs
- D:d ratio of 1:1
- Environmentally friendly
- Light in weight
- Flexible
- Less storage
- Long life cycle
- Access to limited lifting space
- Safer lifting operations
- Improving workflow
- Available in 3t yellow, 5t red, 10t orange, 15t orange and 20t orange
- Available in effective working lengths in the range of 0.5 m up to 16 m

Material: HMPE -Dyneema®

Marking: According to standard, CE-marked Temperature range: -50°C up to +70°C

Standard: EN 1492-2 except material

Safety factor: 7:1

| Part code | WLL ton | EWL m | Colour | Delivery time |
|------------------|------------|----------|--------|---------------|
| 12.20EXHL030005 | 3 | 0.5 | Yellow | 12 |
| 12.20EXHL0300075 | 3 | 0.75 | Yellow | 12 |
| 12.20EXHL030010 | 3 | 1 | Yellow | 12 |
| 12.20EXHL030015 | 3 | 1.5 | Yellow | 12 |
| 12.20EXHL030020 | 3 | 2 | Yellow | 12 |
| 12.20EXHL030025 | 3 | 2.5 | Yellow | 12 |
| 12.20EXHL030030 | 3 | 3 | Yellow | 12 |
| 12.20EXHL030040 | 3 | 4 | Yellow | 12 |
| 12.20EXHL030050 | 3 | 5 | Yellow | 12 |
| | 3 | 6 | Yellow | 12 |
| - | 3 | 7 | Yellow | 12 |
| | 3 | 8 | Yellow | 12 |
| 12.20EXHL050005 | 5 | 0.5 | Red | 12 |
| 12.20EXHL050010 | 5 | 1 | Red | 12 |
| 12.20EXHL050015 | 5 | 1.5 | Red | 12 |
| 12.20EXHL050020 | 5 | 2 | Red | 12 |
| 12.20EXHL050025 | 5 | 2.5 | Red | 12 |
| 12.20EXHL050030 | 5 | 3 | Red | 12 |
| 12.20EXHL050040 | 5 | 4 | Red | 12 |
| 12.20EXHL050050 | 5 | 5 | Red | 12 |
| - | 5 | 6 | Red | 12 |

| - | 5 | 7 | Red | 12 |
|-----------------|----|-----|--------|----|
| - | 5 | 8 | Red | 12 |
| 12.20EXHL100015 | 10 | 1.5 | Orange | 12 |
| 12.20EXHL100020 | 10 | 2 | Orange | 12 |
| 12.20EXHL100030 | 10 | 3 | Orange | 12 |
| 12.20EXHL100040 | 10 | 4 | Orange | 12 |
| 12.20EXHL100050 | 10 | 5 | Orange | 12 |
| - | 10 | 6 | Orange | 12 |
| - | 10 | 0.5 | Orange | 12 |
| - | 10 | 7 | Orange | 12 |

Technical data

Extreema® XS roundsling

HMPE EXS

| WLL | SF | Core ø mm | Weight kg 3m EWL | p/m extra kg |
|-----|----|-----------|------------------|--------------|
| 3t | 7 | 9 | 0,8 | 0,25 |
| 5t | 7 | 14 | 1,35 | 0,43 |
| 10t | 7 | 23 | 2 | 0,65 |
| 15t | 7 | 31 | 3,5 | 1,15 |
| 20t | 7 | 37 | 4,6 | 1,50 |