



Car Lashing VDI 2700 35mm LC 1500daN Comfort handle Swivel and T- hooks

Product information



An auto transporter with a 3-point attachment system that meets VDI 2700 8.1 standards, guaranteeing the safe transport of vehicles. The product provides excellent transmission and uniform distribution of standard tension force (STF). The belt achieves the required performance level of $ETA \geq 0.5$. Minimized belt stretch of 4% ensures reliable load stability, reducing the need for re-tensioning during transport.

The 35mm belt kit includes:

- 35mm polyester belt 2.8m
- Tensioner 35mm, LC 1500daN, STF 330daN
- 2 swivel hooks and 1 T-hook
- Grass type cover 1.3m

Features:

- Performance ETA coefficient ≥ 0.5
- Label with certificate number and inspector's label on the so-called grass cover
- Meets the requirements of EN 12195-2
- According to VDI 2700 8.1, the belt strap must not come into contact with the tire when securing the vehicle. Therefore, rubber or rubber-material protection must be used!

Material: Poliester

Marking: According to standard

Standard: EN 12195-2

Note: Stretchability $\leq 4\%$

Warning: Not for Lifting!

Part code	LC daN	Length m	Band width mm	Fitting	STF daN	Delivery time
-----------	-----------	-------------	------------------	---------	------------	---------------

25041002F	1,500	2.8	35	T-hook	330	12
-----------	-------	-----	----	--------	-----	----