

Secufix - lashing system

Product information



The Secufix suspension belt system offers a quick, safe and simple solution for securing and blocking all types of loads in trucks (semi-trailers and trailers with sliding tarpaulin) in combination with lashing straps according to EN 12195-2 with a width of 50 mm. When securing high loads, the lorry driver no longer has to move the belts from ground level next to the semi-trailer. The suspended belt system enables the load to be secured quickly and safely in one movement. In addition, the load cannot be moved during transport. Fast and efficient. Thanks to the suspension belt system, the load can be fastened and unfastened more quickly.

Key Benefits:

- **One-sided tarpaulin access** - The sliding tarpaulin can be opened from only one side, while straps remain instantly accessible.
- **Immediate readiness** - During loading, straps are always in position and ready to use.
- **Automatic return** - During unloading, flexible return straps automatically guide the belts back into place.
- **No obstruction** - The system allows full use of the trailer's width; belts do not interfere with loading or unloading.
- **Time-saving** - No need to roll up or store belts after unloading, saving up to 30 minutes per load.
- **Durability** - Fully integrated straps mean no risk of loss or premature wear.
- **Easy to use** - The system is intuitive and easy for any driver to learn.
- **Self-installation** - The Secufix system can be easily installed in your fleet without the need for external assistance.

Marking: According to standard

Standard: EN 12195-2

Part code	LC daN	Length m	Width	Description	STF daN	Delivery time
25010559F	2,000	9	50	Lashing to Secufix	375	12
25060128F	-	-	-	Secufix standard set for 4 lashings 8 straps + 8 blocks	-	2