



Endless webbing slings UNV

Product information

Single-layered endless webbing slings are also available with a double layer, which doubles the workload capacity for the same sling width.

Features: RFID-ready

Material: 100% polyester

Marking: According to standard, CE-marked

Temperature range: -40°C - +100 °C

Standard: EN 1492-1

Note: Color coded

Warning: Standard dimensional tolerance is $\pm 3\%$. Lengths can vary within the tolerance range!

Safety factor: 7:1

Part code	WLL ton
UNV101	1
UNV102	1
UNV103	1
UNV104	1
UNV105	1
UNV106	1

UNV108	1
UNV110	1
UNV201	2
UNV202	2
UNV203	2
UNV204	2
UNV205	2
UNV206	2
UNV208	2
UNV210	2
UNV302	3
UNV303	3
UNV304	3
UNV305	3
UNV306	3
UNV308	3
UNV310	3
UNV402	4
UNV403	4
UNV404	4
UNV406	4
UNV408	4
UNV410	4

UNV502	5
UNV503	5
UNV504	5
UNV506	5
UNV508	5
UNV510	5
UNV602	6
UNV604	6
UNV606	6
UNV608	6
UNV610	6
UNV804	8
UNV806	8
UNV808	8
UNV810	8
UNV1004	10
UNV1005	10
UNV1006	10
UNV1010	10