

Extra wide webbing slings 7 - 22,5 t

Product information



We manufacture webbing slings with extra widths, lengths, and forms in our own sewing shop in Finland according to customers' size requirements.

Extra wide webbing slings for paper machine reels and other extra heavy loads. Perfect for when the surface pressure on the load to be lifted should be as low as possible.

Folded reinforced eyes as standard. Elongation with maximum workload approx. 5%.

Note! Standard dimensional tolerance is $\pm 3\%$. Lengths can vary within the tolerance range!

[... Read more](#)

Features: RFID-ready

Material: 100% polyester

Marking: CE-marked

Temperature range: -40°C - +100 °C

Safety factor: 7:1

Extra wide webbing slings 7 - 22,5 t

Technical data

Part code	WLL ton	EWL m	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	Webbing width mm	Eye width mm	Colour
NOM1402	7	2	5.6	14	9.8	7	360	100	Orange
NOM1403	7	3	5.6	14	9.8	7	360	100	Orange
NOM1404	7	4	5.6	14	9.8	7	360	100	Orange
NOM1405	7	5	5.6	14	9.8	7	360	100	Orange
NOM1406	7	6	5.6	14	9.8	7	360	100	Orange
NOM1408	7	8	5.6	14	9.8	7	360	100	Orange
NOM1410	7	10	5.6	14	9.8	7	360	100	Orange
NOM14XX	7	-	5.6	14	9.8	7	360	100	Orange
NOM2202	11	2	8.8	22	15.4	11	600	160	Orange
NOM2203	11	3	8.8	22	15.4	11	600	160	Orange
NOM2204	11	4	8.8	22	15.4	11	600	160	Orange
NOM2205	11	5	8.8	22	15.4	11	600	160	Orange
NOM2206	11	6	8.8	22	15.4	11	600	160	Orange
NOM2208	11	8	8.8	22	15.4	11	600	160	Orange
NOM2210	11	10	8.8	22	15.4	11	600	160	Orange
NOM22XX	11	-	8.8	22	15.4	11	600	160	Orange
NOM3203	16	3	12.8	32	22.4	16	480	130	Orange
NOM3204	16	4	12.8	32	22.4	16	480	130	Orange
NOM3205	16	5	12.8	32	22.4	16	480	130	Orange
NOM3206	16	6	12.8	32	22.4	16	480	130	Orange
NOM3208	16	8	12.8	32	22.4	16	480	130	Orange
NOM3210	16	10	12.8	32	22.4	16	480	130	Orange
NOM32XX	16	-	12.8	32	22.4	16	480	130	Orange
NOM4503	22.5	3	18	45	31.5	22.5	600	160	Orange
NOM4504	22.5	4	18	45	31.5	22.5	600	160	Orange
NOM4505	22.5	5	18	45	31.5	22.5	600	160	Orange
NOM4506	22.5	6	18	45	31.5	22.5	600	160	Orange
NOM4508	22.5	8	18	45	31.5	22.5	600	160	Orange
NOM4510	22.5	10	18	45	31.5	22.5	600	160	Orange
NOM45XX	22.5	-	18	45	31.5	22.5	600	160	Orange