



Round slings assemblies 1-leg

Product information

Lighter alternative to a chain combination in, for example, transformer lifting whitout risk of insulator damage etc. Also available with self-locking hooks, rotating swivel hooks, shackles etc.

Features: RFID-ready Material: 100% polyester Marking: CE-marked

Temperature range: -40°C - +100 °C

Safety factor: 4:1

| Part code | WLL ton | Length | Delivery time |
|-----------|------------|--------|---------------|
| PRK1101 | 1 | 1 | 12 |
| PRK1101.5 | 1 | 1.5 | 12 |
| PRK1102 | 1 | 2 | 12 |
| PRK1102.5 | 1 | 2.5 | 12 |
| PRK1103 | 1 | 3 | 12 |
| PRK1104 | 1 | 4 | 12 |

| PRK2101 | 2 | 1 | 12 |
|-----------|---|-----|----|
| PRK2101.5 | 2 | 1.5 | 12 |
| PRK2102 | 2 | 2 | 12 |
| PRK2102.5 | 2 | 2.5 | 12 |
| PRK2103 | 2 | 3 | 12 |
| PRK2104 | 2 | 4 | 12 |
| PRK3101 | 3 | 1 | 12 |
| PRK3101.5 | 3 | 1.5 | 12 |
| PRK3102 | 3 | 2 | 12 |
| PRK3102.5 | 3 | 2.5 | 12 |
| PRK3103 | 3 | 3 | 12 |
| PRK3104 | 3 | 4 | 12 |
| PRK5101 | 5 | 1 | 12 |
| PRK5101.5 | 5 | 1.5 | 12 |
| PRK5102 | 5 | 2 | 12 |
| PRK5102.5 | 5 | 2.5 | 12 |
| PRK5103 | 5 | 3 | 12 |
| PRK5104 | 5 | 4 | 12 |
| PRK8102 | 8 | 2 | 12 |
| PRK8102.5 | 8 | 2.5 | 12 |
| PRK8103 | 8 | 3 | 12 |
| PRK8104 | 8 | 4 | 12 |
| PRK8105 | 8 | 5 | 12 |