



Round slings assemblies 3-legs

Product information

Lighter alternative to a chain combination in, for example, transformer lifting without risk of insulator damage etc. Also available with self-locking hooks, rotating swivel hooks, shackles etc.

Features: RFID-ready

Material: 100% polyester

Marking: CE-marked

Temperature range: -40°C - +100 °C

Safety factor: 4:1

Part code	WLL ton	WLL 0-45° t	WLL 45-60° t	Length	Delivery time
PRK1301	2.1	2.1	1,5	1	12
PRK1301.5	2.1	2.1	1,5	1.5	12
PRK1302	2.1	2.1	1,5	2	12
PRK1302.5	2.1	2.1	1,5	2.5	12
PRK1303	2.1	2.1	1,5	3	12
PRK1304	2.1	2.1	1,5	4	12

PRK2301	4.2	4.2	3,0	1	12
PRK2301.5	4.2	4.2	3,0	1.5	12
PRK2302	4.2	4.2	3,0	2	12
PRK2302.5	4.2	4.2	3,0	2.5	12
PRK2303	4.2	4.2	3,0	3	12
PRK2304	4.2	4.2	3,0	4	12
PRK3301	6.3	6.3	4,5	1	12
PRK3301.5	6.3	6.3	4,5	1.5	12
PRK3302	6.3	6.3	4,5	2	12
PRK3302.5	6.3	6.3	4,5	2.5	12
PRK3303	6.3	6.3	4,5	3	12
PRK3304	6.3	6.3	4,5	4	12
PRK5301	10.5	10.5	7,5	1	12
PRK5301.5	10.5	10.5	7,5	1.5	12
PRK5302	10.5	10.5	7,5	2	12
PRK5302.5	10.5	10.5	7,5	2.5	12
PRK5303	10.5	10.5	7,5	3	12
PRK5304	10.5	10.5	7,5	4	12
PRK8302	17	17	11,8	2	12
PRK8302.5	17	17	11,8	2.5	12
PRK8303	17	17	11,8	3	12
PRK8304	17	17	11,8	4	12
PRK8305	17	17	11,8	5	12

PRK8306	17	17	11,8	6	12
---------	----	----	------	---	----