

## Single webbing slings 1 - 5 t

---

### Product information



Single layer lifting slings. The width of the sling is high with respect to the workload. Perfect for places, where minimal surface pressure on the load to be lifted is needed, for example when lifting boats. Folded reinforced eyes as standard and also available with flat eyes.

Thanks to our own production unit, we can also make quick deliveries of special types and lengths as well as lifting slings with higher WLL.

... [Read more](#)

---

**Features:** RFID-ready

**Material:** 100% polyester

**Marking:** CE-marked

**Temperature range:** -40°C - +100 °C

**Note:** Color coded

**Warning:** Standard dimensional tolerance is  $\pm 3\%$ . Lengths can vary within the tolerance range!

**Safety factor:** 7:1

## Single webbing slings 1 - 5 t

### Technical data

Part code	WLL ton	EWL m	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	Webbing width mm	Colour
41010076F	1	1	0.8	2	1.4	1	60	Green
41010077F	1	2	0.8	2	1.4	1	60	Green
41010074F	1	3	0.8	2	1.4	1	60	Green
41010078F	1	4	0.8	2	1.4	1	60	Green
41010043F	1	5	0.8	2	1.4	1	60	Green
41010072F	1	6	0.8	2	1.4	1	60	Green
41010063F	1	8	0.8	2	1.4	1	60	Green
41010079F	1	10	0.8	2	1.4	1	60	Green
41010080F	1	12	0.8	2	1.4	1	60	Green
41010081F	1	14	0.8	2	1.4	1	60	Green
41010082F	2	1	1.6	4	2.8	2	120	Grey
41010045F	2	2	1.6	4	2.8	2	120	Grey
41010073F	2	3	1.6	4	2.8	2	120	Grey
41010044F	2	4	1.6	4	2.8	2	120	Grey
41010083F	2	5	1.6	4	2.8	2	120	Grey
41010084F	2	6	1.6	4	2.8	2	120	Grey
41010085F	2	8	1.6	4	2.8	2	120	Grey
41010086F	2	10	1.6	4	2.8	2	120	Grey
41010087F	2	12	1.6	4	2.8	2	120	Grey
41010088F	2	14	1.6	4	2.8	2	120	Grey
41010089F	3	2	2.4	6	4.2	3	180	Brown
41010039F	3	3	2.4	6	4.2	3	180	Brown
41010046F	3	4	2.4	6	4.2	3	180	Brown
41010047F	3	5	2.4	6	4.2	3	180	Brown
41010090F	3	6	2.4	6	4.2	3	180	Brown
41010071F	3	8	2.4	6	4.2	3	180	Brown
41010091F	3	10	2.4	6	4.2	3	180	Brown
41010092F	3	12	2.4	6	4.2	3	180	Brown
41010093F	3	14	2.4	6	4.2	3	180	Brown
41010094F	4	2	3.2	8	5.6	4	240	Blue
41010095F	4	3	3.2	8	5.6	4	240	Blue

## Single webbing slings 1 - 5 t

### Technical data

Part code	WLL ton	EWL m	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	Webbing width mm	Colour
41010034F	4	4	3.2	8	5.6	4	240	Blue
41010096F	4	5	3.2	8	5.6	4	240	Blue
41010033F	4	6	3.2	8	5.6	4	240	Blue
41010097F	4	8	3.2	8	5.6	4	240	Blue
41010098F	4	10	3.2	8	5.6	4	240	Blue
41010099F	4	12	3.2	8	5.6	4	240	Blue
41010100F	4	14	3.2	8	5.6	4	240	Blue
41010050F	5	3	4	10	7	5	300	Orange
41010101F	5	4	4	10	7	5	300	Orange
41010102F	5	5	4	10	7	5	300	Orange
41010048F	5	6	4	10	7	5	300	Orange
41010103F	5	8	4	10	7	5	300	Orange
41010060F	5	10	4	10	7	5	300	Orange
41010104F	5	12	4	10	7	5	300	Orange
41010105F	5	14	4	10	7	5	300	Orange