



Single webbing slings 1 - 5 t

Product information

Single layer lifting slings. The width of the sling is high with respect to the workload. Perfect for places, where minimal surface pressure on the load to be lifted is needed, for example when lifting boats. Folded reinforced eyes as standard and also available with flat eyes.

Thanks to our own production unit, we can also make quick deliveries of special types and lengths as well as lifting slings with higher WLL.

Features: RFID-ready

Material: 100% polyester

Marking: CE-marked

Temperature range: -40°C - +100 °C

Note: Color coded

Warning: Standard dimensional tolerance is $\pm 3\%$. Lengths can vary within the tolerance range!

Safety factor: 7:1

Part code	WLL ton	EWL m	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	Webbing width mm	Colour	Delivery time
41010076F	1	1	0.8	2	1.4	1	60	Green	12
41010077F	1	2	0.8	2	1.4	1	60	Green	12
41010074F	1	3	0.8	2	1.4	1	60	Green	12
41010078F	1	4	0.8	2	1.4	1	60	Green	12
41010043F	1	5	0.8	2	1.4	1	60	Green	12
41010072F	1	6	0.8	2	1.4	1	60	Green	12

41010063F	1	8	0.8	2	1.4	1	60	Green	12
41010079F	1	10	0.8	2	1.4	1	60	Green	12
41010080F	1	12	0.8	2	1.4	1	60	Green	12
41010081F	1	14	0.8	2	1.4	1	60	Green	12
41010082F	2	1	1.6	4	2.8	2	120	Grey	12
41010045F	2	2	1.6	4	2.8	2	120	Grey	12
41010073F	2	3	1.6	4	2.8	2	120	Grey	12
41010044F	2	4	1.6	4	2.8	2	120	Grey	12
41010083F	2	5	1.6	4	2.8	2	120	Grey	12
41010084F	2	6	1.6	4	2.8	2	120	Grey	12
41010085F	2	8	1.6	4	2.8	2	120	Grey	12
41010086F	2	10	1.6	4	2.8	2	120	Grey	12
41010087F	2	12	1.6	4	2.8	2	120	Grey	12
41010088F	2	14	1.6	4	2.8	2	120	Grey	12
41010089F	3	2	2.4	6	4.2	3	180	Brown	12
41010039F	3	3	2.4	6	4.2	3	180	Brown	12
41010046F	3	4	2.4	6	4.2	3	180	Brown	12
41010047F	3	5	2.4	6	4.2	3	180	Brown	12
41010090F	3	6	2.4	6	4.2	3	180	Brown	12
41010071F	3	8	2.4	6	4.2	3	180	Brown	12
41010091F	3	10	2.4	6	4.2	3	180	Brown	12
41010092F	3	12	2.4	6	4.2	3	180	Brown	12
41010093F	3	14	2.4	6	4.2	3	180	Brown	12

41010094F	4	2	3.2	8	5.6	4	240	Blue	12
41010095F	4	3	3.2	8	5.6	4	240	Blue	12
41010034F	4	4	3.2	8	5.6	4	240	Blue	12
41010096F	4	5	3.2	8	5.6	4	240	Blue	12
41010033F	4	6	3.2	8	5.6	4	240	Blue	12
41010097F	4	8	3.2	8	5.6	4	240	Blue	12
41010098F	4	10	3.2	8	5.6	4	240	Blue	12
41010099F	4	12	3.2	8	5.6	4	240	Blue	12
41010100F	4	14	3.2	8	5.6	4	240	Blue	12
41010050F	5	3	4	10	7	5	300	Orange	12
41010101F	5	4	4	10	7	5	300	Orange	12
41010102F	5	5	4	10	7	5	300	Orange	12
41010048F	5	6	4	10	7	5	300	Orange	12
41010103F	5	8	4	10	7	5	300	Orange	12
41010060F	5	10	4	10	7	5	300	Orange	12
41010104F	5	12	4	10	7	5	300	Orange	12
41010105F	5	14	4	10	7	5	300	Orange	12