Manhole Clamp

Product information



The manhole clamp is used for the transport and laying of manholes. No adjustment of the clamping range is necessary. Accidents caused by incorrect adjustment are excluded. Due to the holdfast application the clamp must not be lifted when applying and disconnecting.

Features:

- Simple applying and disconnecting by means of holdfast application: clamp must not be lifted manually
- No adjustment of the clamping range
- Huge multiplication guarantees optimum safety
- Manhole clamp SZA for manholes and cones according to DIN 4034 Part 1 and 2
- With spring tension
- With web sling or high-strength chains

... *Read more*

Safety factor: 5:1

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Manhole Clamp

Technical data

Part code	Code	WLL ton	Jaw width mm	Weight kg
44000177B	SZM 1	1	40-120	16
44000178B	SZM 1.5	1.5	40-120	28
44000179B	SZML 1.5	1.5	40-120	29
44000184B	SZM 1.5 K	1.5	40-120	32
44000180B	SZA 2	2	60-180	28
44000185B	SZA 2K	2	60-180	31
44000181B	SZA 3	3	60-180	40
44000182B	SZAL 3	3	60-180	41
44000186B	SZA 3 K	3	60-180	45
44000187B	SZAL 3 K	3	60-180	47
44000183B	SZA 4	4	60-180	55

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved