

Lifting Eye Nut NS8M, grade 80



Product information

Lifting for all lifting directions.

WLL for horizontal lifting is marked on the eye.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40°C - +200°C

Finish: Painted, yellow

Standard: EN 1677-1

Safety factor: 4:1

Part code	WLL ton	Thread mm	Eye diameter mm	Thread pitch mm	D,	L	M mm	ø mm	Weight kg	Delivery time
46010001F	0.4	M6	20	1	36	36	M6	20	0.05	2
46010002F	0.8	M8	20	1,25	36	36	M8	20	0.05	2
46010003F	1	M10	25	1,5	45	45	M10	25	0.09	2
46010004F	2	M12	30	1,75	54	53	M12	30	0.16	2
46010005F	3	M14	35	2	63	62	M14	35	0.24	2
46010006F	4	M16	35	2	63	62	M16	35	0.24	2
46010007F	6	M20	40	2,5	72	71	M20	40	0.36	2
46010008F	8	M24	50	3	90	90	M24	50	0.72	2
46010009F	12	M30	60	3,5	108	109	M30	60	1.32	2
46010010F	16	M36	70	4	126	128	M36	70	2.08	2
46010011F	24	M42	80	4,5	144	147	M42	80	3.11	12
46010012F	32	M48	90	5	166	168	M48	90	5.02	12

Technical data

Size	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	Tightening torgue
M6	0,4	0,15	0,8	0,3	0,21	0,15	0,32	0,23	3,5
M8	0,8	0,32	1,6	0,64	0,448	0,32	0,672	0,48	8
M10	1	0,4	2	0,8	0,56	0,4	0,84	0,6	16
M12	2	0,75	4	1,5	1,05	0,75	1,58	1,13	28
M14	3	1,2	6	2,4	1,68	1,2	2,52	1,8	70
M16	4	1,5	8	3	2,1	1,5	3,15	2,25	70
M20	6	2,3	12	4,6	3,22	2,3	4,83	3,45	135
M24	8	3,2	16	6,4	4,48	3,2	6,72	4,8	230
M30	12	4,5	24	9	6,3	4,5	9,45	6,75	465
M36	16	7	32	14	9,8	7	14,7	10,5	814
M42	24	9	48	18	12,6	9	18,9	13,5	1304
M48	32	12	64	24	16,8	12	25,2	18	1981

Blueprint

