Forankra
Zabezpieczamy wszystko w transporcie™

Stainless steel Lifting eye screw NSRHL DIN 580

Product information

Stainless steel lifting eye for vertical lifting.

Material: AISI 316
Marking: According to standard, CE-marked
Temperature range: -40°C - (+)200°C
Finish: Polished
Standard: DIN 580
Note: Only for vertical lifting
Warning: Not to be heat-treated

Safety factor: 4:1

Part Code	WLL ton	Thread mm	b mm	c mm	d mm	e mm	f mm	g mm	Weight kg	Delivery time
NSRH06L	0.08	M6	20	36	20	13	6	36	0.06	12
NSRH08L	0.14	M8	20	36	20	13	6	36	0.06	12
NSRH10L	0.23	M10	25	45	25	17	8	45	0.11	12
48020002F	0.34	M12	30	54	30	20.5	10	53	0.18	12
NSRH16L	0.7	M16	35	63	35	27	12	62	0.28	12
NSRH20L	1.2	M20	39	71	39	30	14	70	0.45	12

Technical data

WORKIN LOAD LIMITS

Thread	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)
					0 - 45°	45-60°	0 - 45°	45-60°
M6	0,08		0,16		-		-	
M8	0,14		0,28		0,1		0,14	
M10	0,23		0,46					

Blueprint