Forankra
Zabezpieczamy wszystko w transporcie™

Stainless steel Lifting eye screw NSRHL DIN 580

Product information



Stainless steel lifting eye for vertical lifting.

... *Read more*

Material: AISI 316
Marking: According to standard, CE-mark
Temperature range: -40°C - (+)200°C
Finish: Polished
Standard: DIN 580
Note: Only for vertical lifting
Warning: Not to be heat-treated

Safety factor: 4:1


Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Stainless steel Lifting eye screw NSRHL DIN 580

Blueprint



Technical data

Part code	WLL ton	Thread mm	b mm	c mm	d mm	e mm	f mm	g mm	Weight kg
NSRH06L	0.075	M6	20	36	20	13	6	36	0.06
48020011F	0.14	M8	20	36	20	13	6	36	0.06
48020006F	0.23	M10	25	45	25	17	8	45	0.11
48020002F	0.34	M12	30	54	30	20.5	10	53	0.18
48020003F	0.7	M16	35	63	35	27	12	62	0.28
48020004F	1.2	M20	39	71	39	30	14	70	0.45

WORKIN LOAD LIMITS

Thread	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)
					0 - 45°	45-60°	0 - 45°	45-60°
M6	0,08		0,16		-		-	
M8	0,14		0,28		0,1		0,14	
M10	0,23		0,46					

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved