

## Eye Point Stainless Steel 8-S291

---

### Product information



- Rotates through 360° adjustable in the direction of the load.
- Individual forged parts and cap screw are traceable to Test Certification.
- Bolts are Metric thread.
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Quick and simple assembly, just a tapped hole is required.
- Used in different applications such as chemical oil coal industries, food processing,

... [Read more](#)

---

**Material:** Stainless Steel

**Marking:** According to standard, CE-marked


**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 10

## Eye Point Stainless Steel 8-S291

### Blueprint



### Technical data

Part code	WLL ton	Thread mm	Torque Nm	Pitch DIN13	A mm	B mm	C mm	D mm	F mm	G mm	H mm	J mm	S mm	W mm	M mm	E mm	Weight kg
11.428-S291-005	0.5	M12	10	1.75	45	30	10	11	33	29	5	44	8	52	M12	18	0.2
11.428-S291-010	1	M16	30	2	52	35	14	13	35	33	5	51	10	61	M16	24	0.3
11.428-S291-020	2	M20	70	2.5	60	40	16	15	44	37	7	60	12	70	M20	30	0.6
11.428-S291-025	2.5	M24	150	3	72	49	19	18	52	46	10	72	14	84	M24	36	1