



## Chain sling 4-legs with safety hooks and grab hooks, grade 80

### Product information

4-legs chain sling assembly equipped with safety hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

<b>Part code</b>	<b>Chain diameter mm</b>	<b>WLL 0-45° t</b>	<b>WLL 45-60° t</b>	<b>Delivery time</b>
NKV06401L	6	2.36	1.7	12
NKV07401L	7	3.15	2.24	12
NKV08401L	8	4.25	3	12
NKV10401L	10	6.7	4.75	12
NKV13401L	13	11.2	8	12
NKV16401L	16	17	11.8	12
NKV20401L	20	26.5	19	12
NKV22401L	22	31.5	22.4	12
NKV26401L	26	45	31.5	12
NKV32401L	32	67	47.5	12

## Blueprint

