



Connection link LLA, grade 100

Product information

Attachment to the master link with a separate chain, to which the clutch is fixed with a pin. Can be used for normal shortening or for making a loop around the item to be lifted. Equipped with a chain locking pin.

Material: Steel

Marking: CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, blue

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

| Part code | WLL ton | For chain Ø mm | D mm | K mm | A mm | Weight kg | Delivery time |
|-----------|---------|----------------|------|------|------|-----------|---------------|
| 42050020F | 1.4 | 6 | 7 | 44 | 14 | 0.1 | 2 |
| 42050023F | 2.5 | 8 | 10 | 61 | 18 | 0.22 | 2 |
| 42050007F | 4 | 10 | 12 | 72 | 23 | 0.45 | 2 |
| 42050009F | 6.7 | 13 | 16 | 89 | 27 | 1.15 | 2 |
| 42050012F | 10 | 16 | 21 | 103 | 33 | 1.75 | 2 |
| 42050015F | 16 | 20 | 24 | 116 | 42 | 2.7 | 2 |
| 42050016F | 19 | 22 | 27 | 135 | 48 | 4.02 | 2 |

Blueprint

