

Connection link LL, grade 80



Product information

Connecting link is used for connecting short link grade 80 chains to different components in a lifting sling.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-1

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

| Part code | WLL ton | EWL mm | For chain Ø mm | L | K, | A, | D, | Weight kg | Delivery time |
|-----------|---------|--------|----------------|-----|-----|----|----|-----------|---------------|
| 42040044F | 1.12 | 42 | 6 | 58 | 42 | 15 | 7 | 0.08 | 2 |
| 42040046F | 2 | 60 | 7-8 | 79 | 60 | 18 | 8 | 0.146 | 2 |
| 42040034F | 3.15 | 68 | 10 | 90 | 68 | 25 | 11 | 0.3 | 2 |
| 42040036F | 5.3 | 87 | 13 | 117 | 87 | 29 | 15 | 0.65 | 2 |
| 42040038F | 8 | 108 | 16 | 148 | 108 | 34 | 19 | 1.15 | 2 |
| 42040040F | 12.5 | 121 | 20 | 154 | 121 | 41 | 24 | 2.1 | 2 |
| 42040041F | 15 | 141 | 22 | 193 | 141 | 48 | 26 | 2.87 | 2 |
| 42040042F | 21.2 | 158 | 26 | 220 | 158 | 57 | 30 | 4.5 | 2 |
| 42040043F | 31.5 | 205 | 32 | 281 | 205 | 67 | 37 | 8.21 | 2 |

Blueprint

