



## Foundry eye hook VAL, grade 80

### Product information

Foundry eye hook with a wide mouth opening are attached to the chain with connecting slings.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-1

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

Part code	WLL ton	EWL mm	For chain Ø mm	P mm	H mm	K mm	D mm	A mm	M mm	Weight kg	Delivery time
46060014F	1.12	124	6	62	29	163	17	39	26	1	2
46060016F	2	122	7/8	63	31	163	18	39	25	1.09	12
46060004F	3.15	150	10	76	38	200	22	50	32	2.04	12
46060006F	5.3	180	13	89	44	238	27	63	38	3.22	12
46060008F	8	210	16	102	52	278	32	76	46	5.53	2
46060010F	12.5	240	20	114	65	325	38	89	55	8.75	12
46060011F	15	272	22	127	69	361	45	102	57	11.93	2
46060012F	21.2	302	26	140	77	402	67	126	66	16.8	12
46060013F	31.5	340	32	153	97	461	81	151	80	26.6	12

## Blueprint

