Latch hook with ball bearing swivel SALKLKL, grade 80

Product information



Hook is equipped with spring loaded safety latch. Due to the swivel the hook is easy to align into the wanted direction.

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-2
Warning: Not to be heat-treated

Safety factor: 4:1
Grade: 8

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Latch hook with ball bearing swivel SALKLKL, grade 80

Blueprint



Technical data

Part code	WLL ton	EWL mm	For chain Ø mm	A mm	B mm	E mm	K mm	H mm	Weight kg
42040327F	1.12	-	6	31,5	24	22,5	112	19,5	0.65
42040202F	2	170	8	44,5	41	25	152,5	26	0.95
42040193F	3.15	207	10	44,5	41	25	161	30	1.71
42040195F	5.3	248	13	50,5	43,5	35	188,5	37	3.13
42040197F	8	295	16	63,5	58,5	43	243	46,5	5.44
42040326F	12.5	356	20	70	67	53	286	56,5	9.5

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved