Master link NOR, grade 80

Product information



Masterlink for chain sling assemblies. ... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-4
Warning: Not to be heat-treated

Safety factor: 4:1
Grade: 8


Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved

Forankra
Zabezpieczamy wszystko w transporcie™

Master link NOR, grade 80

Blueprint



Technical data

Part code	WLL ton	EWL mm	For chain, 1-leg mm	For chain, 2-leg mm	A mm	B mm	D mm	Weight kg
42040090F	1.6	110	6/7	6	110	60	13	0.34
42040093F	2.12	110	8	7	110	60	16	0.53
42040069F	3.15	135	10	8	135	75	18	0.8
42040071F	5.3	160	13	10	160	90	22	1.5
42040073F	8	180	16	13	180	100	26	2.3
42040075F	11.2	200	18	16	200	110	32	3.9
42040317F	14	260	20	18	260	140	36	6.35
42040078F	17	300	22	20	300	160	40	9
42040080F	21.2	340	26	22	340	180	45	12.8
42040082F	31.5	350	32	26	350	190	50	17.2
42040084F	45	400	36	32	400	200	56	24.2

Forankra Polska
office@forankra.pl
+48 91 418 25 91

© November 2026 - All Rights Reserved